## **Datasheet**

## REGIOLUX

Category (ETIM): Variable device mount

Type: Device mount IP20-SDGVLT LED

Order number: 18324506650

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver DALI (1 pcs.)

Mains voltage:230V / 50HzSystem performance (W):47Luminaire luminous flux (Im):7500Im/W:159Ambient temperatures:10°C / 40°C

7 till blonk tomporataroo.

Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Colour of the housing: traffic white RAL 9016

Weight (net) (kg): 2.1

Dimensions LxWxH/DxH (mm): 1531 x 55 x 41


mounting method: Mounting rail system mounting

EAN-number: 4020863336142 Commodity code: 94051098

## SDGVLT LED 7500lm 840 • vw • DALI • 18324506650



Lighting technology Linear.Lens.Profil-direct narrow distribution SDGVLT LED 7500 lm 840



 $\begin{array}{lll} \eta LB & 100 \ \% \\ Im/W & 159 \\ \Phi \downarrow / \uparrow & 99 \ \% \ / \ 1 \ \% \\ UGR \ q/I & 20.8 \ / \ 28.3 \end{array}$ 



Quick-fit mounting system Variable device mount; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated lateral lever locks. LED unit in housing length for optically seamless light run. Can be variably positioned on the mounting rail. Housing colour traffic white RAL 9016; Direct narrow light distribution using Linear.Lens.Profil made of clear PMMA plastic. Optically seamless light run. Heat-resistant cables including connection cable 1 m and rapid installation plug connector with tool-less phase pre-selection and locating finger.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 41

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour

rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 7500

Im/W: 159

Operating device: Electronic driver DALI (1 pcs.)

System performance (W): 47

Conditions: Suitable for use in ambient temperatures of 10°C to 40°C Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Regiolux GmbH

Type: SDGVLT LED 7500 840 DALI vw

Article number: 18324506650

Product deep link: http://www.regiolux.de/de/article/18324506650

5 year guarantee after registration on website.