


|                               |                                                                                                                        |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Category (ETIM):              | Mounted luminaire                                                                                                      |
| Type:                         | stail-SAX LED                                                                                                          |
| Order number:                 | 60321024160                                                                                                            |
| Configuration:                | Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10 |
| Operating device:             | Electronic driver (1 pcs.)                                                                                             |
| Mains voltage:                | 230V / 50Hz                                                                                                            |
| System performance (W):       | 34                                                                                                                     |
| Luminaire luminous flux (lm): | 3200                                                                                                                   |
| lm/W:                         | 96                                                                                                                     |
| Energy efficiency class:      | A+                                                                                                                     |
| Certifications:               | IP 20, protection class I, BAP 65°<1500, F, Indoor, CE                                                                 |
| Colour of the housing:        | traffic white RAL 9016                                                                                                 |
| Weight (net) (kg):            | 3.35                                                                                                                   |
| Dimensions LxWxH/DxH (mm):    | 1240 x 151 x 56                                                                                                        |
| Cable entry KE X/Y (mm):      | 0 / 30                                                                                                                 |
| mounting method:              | Surface single mounting, Surface light run mounting, Mounting rail mounting                                            |
| EAN-number:                   | 4020863307111                                                                                                          |
| Commodity code:               | 94051098                                                                                                               |

## stail-SAX/1200-1 LED 3200lm 840 • vw • ED • 60321024160




### Lighting technology

Micro-parabolic louvre, silky matt-direct distribution  
SAX/1200-1 LED 3200 lm 840




|         |                 |
|---------|-----------------|
| ηLB     | 100 %           |
| lm/W    | 96              |
| Φ ↓/↑   | 100 % / 0 %     |
| UGR q/l | 20.7 / 20.0     |
| BAP     | 65° < 1500cd/m² |



Mounted luminaire; Sheet steel housing, flat rectangular cross section, visible installation height 26 mm with 30 mm clearance from the ceiling; end faces made of steel; Housing colour traffic white RAL 9016; Direct light distribution using reflectivity-enhanced parabolic aluminium louvre, silk matt with low installation height cross blades, for workstations, omnidirectional glare reduction according to the current DIN-EN 12464-1 standard, self-engaging. Electrical connection via 3-pole connection terminal with plug-in contacts.

Dimensions LxWxH/DxH (mm): 1240 x 151 x 56  
Cable entry KE X/Y (mm): 0 / 30  
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10  
Luminaire luminous flux (lm): 3200  
lm/W: 96  
Operating device: Electronic driver (1 pcs.)  
System performance (W): 34  
Energy efficiency class: A+  
Certifications: IP 20, protection class I, BAP 65°<1500, F, Indoor, CE



Regiolux GmbH  
Type: stail-SAX/1200-1 LED 3200 840 ET vw  
Article number: 60321024160  
Product deep link: <http://www.regiolux.de/en/article/60321024160>  
5 year guarantee after registration on website.