

Category (ETIM):	Wall luminaire
Type:	visula-VSWIG LED
Order number:	43611046615
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	27
Luminaire luminous flux (lm):	2300
lm/W:	86
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, F, Indoor, CE
Colour of the housing:	aluminium natural anodized
Weight (net) (kg):	4.15
Dimensions LxWxH/DxH (mm):	635 x 330 x 42
Cable entry KE X/Y (mm):	0 / 0
mounting method:	Wall surface-mounting, Surface single mounting
EAN-number:	4020863314782
Commodity code:	94051098


visula-VSWIG/635 LED 2300lm 840 • aen • DALI • 43611046615




Lighting technology

Diffuser, frosted-Direct distribution/ indirect distribution for wall lighting

VSWIG/635 LED 2300 lm 840



ηLB	100 %
lm/W	86
Φ ↓/↑	84 % / 16 %



Wall luminaire; Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 42 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the front of the luminaire. Housing colour aluminium natural anodized; Direct/indirect light distribution, direct component using frosted PMMA pane, homogeneous light emission through lateral LED light coupling and aluminium reflector fitted on top of it in a highly reflective white coating, with micro perforation for easy wall lighting. Integrated LED driver design. Electrical connection and connection of control cable using 5-pole connection terminal with plug-in contacts.

Dimensions LxWxH/DxH (mm): 635 x 330 x 42
 Cable entry KE X/Y (mm): 0 / 0
 Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
 Luminaire luminous flux (lm): 2300
 lm/W: 86
 Operating device: Electronic driver DALI (1 pcs.)
 System performance (W): 27
 Energy efficiency class: A+
 Certifications: IP 20, protection class I, F, Indoor, CE

Regiolux GmbH
 Type: visula-VSWIG/635 LED 2300 840 DALI aen
 Article number: 43611046615
 Product deep link: <http://www.regiolux.de/en/article/43611046615>
 5 year guarantee after registration on website.

