

Category (ETIM):	Mounted luminaire
Type:	visula-VSAIG LED
Order number:	43321016615
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	54
Luminaire luminous flux (lm):	4900
lm/W:	91
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, F, Indoor, CE
Colour of the housing:	aluminium natural anodized
Weight (net) (kg):	7.6
Dimensions LxWxH/DxH (mm):	1199 x 330 x 42
Cable entry KE X/Y (mm):	0 / 0
mounting method:	Surface single mounting
EAN-number:	4020863308552
Commodity code:	94051098


visula-VSAIG/1200 LED 4900lm 840 • aen • DALI • 43321016615




Lighting technology

Diffuser, frosted-direct/indirect distribution for ceiling lighting

VSAIG/1200 LED 4900 lm 840



ηLB	100 %
lm/W	91
Φ ↓/↑	84 % / 16 %
UGR q/l	20.2 / 20.0



Mounted luminaire; Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 30 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the bottom of the luminaire. Housing colour aluminium natural anodized; Light distribution direct/indirect distribution, direct component using frosted pane made of PMMA, homogeneous light emission by lateral LED light coupling and fitted aluminium reflector in highly reflective white coating, with micro-perforation for a moderate ceiling illumination. Integrated LED driver design. Electrical connection and connection of control cable using 5-pole connection terminal with plug-in contacts.

Dimensions LxWxH/DxH (mm): 1199 x 330 x 42

Cable entry KE X/Y (mm): 0 / 0

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 4900

lm/W: 91

Operating device: Electronic driver DALI (1 pcs.)

System performance (W): 54

Energy efficiency class: A+

Certifications: IP 20, protection class I, F, Indoor, CE

Regiolux GmbH

Type: visula-VSAIG/1200 LED 4900 840 DALI aen

Article number: 43321016615

Product deep link: <http://www.regiolux.de/en/article/43321016615>

5 year guarantee after registration on website.

