Datasheet

REGIOLUX

Category (ETIM): Suspended luminaire Type: visula-VSHIMP LED Order number: 43251024175

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver (1 pcs.)

Mains voltage: 230V / 50Hz System performance (W): 67 Luminaire luminous flux (lm): 6100 90

Energy efficiency class:

IP 20, protection class I, BAP 65°<3000, F, Indoor, CE Certifications:

Colour of the housing: aluminium natural anodized

Weight (net) (kg):

Dimensions LxWxH/DxH (mm): 1480 x 330 x 30

mounting method: Suspended single mounting

EAN-number: 4020863304462 94051098 Commodity code:


visula-VSHIMP/1500 LED 6100lm 840 • aen • ED • 43251024175



Lighting technology Diffuser, micro-prismatic-direct/indirect distribution VSHIMP/1500 LED 6100 Im 840


 $\eta L B$


BAP



100 % lm/W 90 Φ ⊥/↑ ŪĞR q/I

84 % / 16 % 18.1 / 18.2 65° < 3000cd/m²





Suspended luminaire; Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 30 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the bottom of the luminaire. Housing colour aluminium natural anodized; Direct/indirect light distribution, direct component using microprism made of PMMA, homogeneous light emission through lateral LED light coupling and overlying aluminium reflector with highly reflective white coating, with micro-perforation for the indirect light component; for workstations, omnidirectional glare suppression according to the current DIN-EN 12464-1 standard. Integrated LED driver design. Electrical connection via integrated transparent connection cable 3 x 0.75 mm², length 2300 mm, stripped cable ends. Suspension included

Dimensions LxWxH/DxH (mm): 1480 x 330 x 30

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 6100

Im/W: 90

Operating device: Electronic driver (1 pcs.)

System performance (W): 67 Energy efficiency class: A+

Certifications: IP 20, protection class I, BAP 65°<3000, F, Indoor, CE

Regiolux GmbH

Type: visula-VSHIMP/1500 LED 6100 840 ET aen

Article number: 43251024175

Product deep link: http://www.regiolux.de/en/article/43251024175

5 year guarantee after registration on website.