


Category (ETIM):	Variable device mount
Type:	Device mount IP40-SDGV LED
Order number:	18201016650
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	35
Luminaire luminous flux (lm):	4200
lm/W:	121
Energy efficiency class:	A+
Ambient temperatures:	10°C / 35°C
Certifications:	IP 40, protection class I, F, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2
Dimensions LxWxH/DxH (mm):	1531 x 55 x 43
mounting method:	Mounting rail system mounting
EAN-number:	4020863269631
Commodity code:	94051098


SDGV LED 4200lm 840 • vw • DALI • 18201016650



Lighting technology
open distribution-general diffuse
SDGV LED 4200 lm 840



ηLB	100 %
lm/W	121
Φ ↓/↑	100 % / 0 %
UGR q/l	25.9 / 26.9



Quick-fit mounting system Variable device mount; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated rotary catches. LED unit made of naturally anodised extruded aluminium profile with end faces made of plastic. Suitable for the mounting of LED light directing components. Can be variably positioned on the mounting rail. Housing colour traffic white RAL 9016; Direct, general diffuse light distribution. LED diffuser cover made of polycarbonate. Heat-resistant cables including connection cable 1 m and rapid installation plug connector with tool-free phase preselection and locating finger. Can be combined with the self-supporting specular reflectors S DFA LED, S DFB LED, S DFT LED und S DFH LED.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 43
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 4200
lm/W: 121
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 35
Energy efficiency class: A+
Conditions: Suitable for use in ambient temperatures of 10°C to 35°C
Certifications: IP 40, protection class I, F, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGV LED 4200 840 DALI vw
Article number: 18201016650
Product deep link: <http://www.regiolux.de/de/article/18201016650>
5 year guarantee after registration on website.