


Category (ETIM):	Recessed luminaire
Type:	hokal-HLEG LED
Order number:	60523024180
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	42
Luminaire luminous flux (lm):	3700
lm/W:	87
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	3.7
Dimensions LxWxH/DxH (mm):	1476 x 84 x 76
Depth (mm):	72
Ceiling system:	cut-out ceilings [AD], Panel ceiling [PD] (module 100)
Necessary depth min. (mm):	155(AD)
Ceiling cut-out LxW/D (mm):	x 74
mounting method:	Ceiling recessing single mounting, Ceiling recessing light run mounting
EAN-number:	4020863319053
Commodity code:	94051098


hokal-HLEG/1500-1 LED 3700lm 840 • vw • ED • 60523024180



Lighting technology
Diffuser, satined-direct distribution
HLEG/1500-1 LED 3700 lm 840



ηLB	100 %
lm/W	87
Φ ↓/↑	100 % / 0 %
UGR q/l	25.4 / 25.5



Recessed luminaire; Sheet steel housing suitable for recessed ceilings and panel ceilings; prepared for fixing of end faces or for mounting in light run arrangements; white coated, similar to RAL 9016; Housing colour traffic white RAL 9016; Direct light distribution; glare suppression using diffuse distribution frosted polycarbonate profile; diffuser is optically seamless for light run mounting; Electrical connection via 3-pole connection terminal with plug-in contacts. Integrated driver. Required accessories: end faces and universal attachment clips UBD for cut-out ceilings or WSPHL for panel ceilings; please order separately.

Dimensions LxWxH/DxH (mm): 1476 x 84 x 76
Ceiling system: cut-out ceilings [AD], Panel ceiling [PD] (module 100)
Necessary depth min. (mm): 155(AD)
Ceiling cut-out LxW/D (mm): x 74
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 3700
lm/W: 87
Operating device: Electronic driver (1 pcs.)
System performance (W): 42
Energy efficiency class: A+
Certifications: IP 20, protection class I, F, Indoor, CE

Regiolux GmbH
Type: hokal-HLEG/1500-1 LED 3700 840 ET vw
Article number: 60523024180
Product deep link: <http://www.regiolux.de/en/article/60523024180>
5 year guarantee after registration on website.

