

Datasheet


REGIOLUX

Category (ETIM):	Suspended luminaire
Type:	hokal-HLHIG LED
Order number:	60513026685
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	44
Luminaire luminous flux (lm):	3400
lm/W:	77
Energy efficiency class:	A
Certifications:	IP 20, protection class I, ENEC10 VDE, F, Indoor, CE
Colour of the housing:	silver-grey
Weight (net) (kg):	3.7
Dimensions LxWxDxH (mm):	1476 x 85 x 72
mounting method:	Suspended single mounting, Suspended / light run mounting
EAN-number:	4020863319138
Commodity code:	94051098


hokal-HLHIG/1500 LED 3400lm 840 • sg • DALI • 60513026685



Lighting technology
Diffuser, satined-direct/indirect distribution
HLHIG/1500 LED 3400 lm 840



ηLB	100 %
lm/W	77
Φ ↓/↑	65 % / 35 %
UGR q/l	20.8 / 20.9



Suspended luminaire; Sheet steel housing with square design; prepared for fixing end faces or luminaire connectors made of steel; Housing colour silver-grey; Direct/indirect light distribution; glare suppression using diffuse distribution frosted polycarbonate profile; diffuser is optically seamless for light run mounting; Electrical connection and connection of control cable using 5-pole connection terminal with plug-in contacts. Required accessories: order face ends, connectors, through-wiring and Y-wire suspensions SAY-KS/SAYE-KL with 2000 mm suspension length separately according to luminaire arrangements.

Dimensions LxWxDxH (mm): 1476 x 85 x 72
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 3400
lm/W: 77
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 44
Energy efficiency class: A
Certifications: IP 20, protection class I, ENEC10 VDE, F, Indoor, CE

Regiolux GmbH
Type: hokal-HLHIG/1500 LED 3400 840 DALI sg
Article number: 60513026685
Product deep link: <http://www.regiolux.de/en/article/60513026685>
5 year guarantee after registration on website.

