


Category (ETIM):	Device mount IP 54
Type:	Device mount IP54-SDGSOH LED
Order number:	18640406600
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	75
Luminaire luminous flux (lm):	10000
lm/W:	129
Energy efficiency class:	A++
Ambient temperatures:	-20°C / 25°C
Certifications:	IP 54, protection class I, BAP 65°<3000, F, D, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	1.9
Dimensions LxWxH/DxH (mm):	1531 x 55 x 37
mounting method:	Mounting rail system mounting
EAN-number:	4020863326082
Commodity code:	94051098


SDGSOH LED 10000lm 840 • vw • DALI • 18640406600



Lighting technology
Individual.Lens.Optic-direct extremely narrow distribution
SDGSOH LED 10000 lm 840



ηLB	100 %
lm/W	129
Φ ↓/↑	99 % / 1 %
UGR q/l	13.4 / 12.0
BAP	65° < 3000cd/m²



Quick-fit mounting system Device mount IP 54; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated pressure locks. Lighttechnical element with transparent seal, end faces made of plastic, all-round closed seal to mounting rail. Housing colour traffic white RAL 9016; Extremely direct narrow-beam light distribution with controlled rack lighting using individual. lens. optic made of PMMA plastic. Continuous optics. Uniform LED spacing, even across circuit boards. 3-row LED arrangement. Light direction components are easy to maintain due to smooth surface which is easily cleaned. Heat-resistant cables including fixed 5-pole rapid installation plug connector with tool-less phase pre-selection and locating finger.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 37
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 10000
lm/W: 129
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 75
Energy efficiency class: A++
Conditions: Suitable for use in ambient temperatures of -20°C to 25°C
Certifications: IP 54, protection class I, BAP 65°<3000, F, D, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGSOH LED 10000 840 DALI vw
Article number: 18640406600
Product deep link: <http://www.regiolux.de/de/article/18640406600>
5 year guarantee after registration on website.