


Category (ETIM):	diffuser luminaire
Type:	WBLR LED
Order number:	25310144110
Configuration:	Lamps integrated: LED, Light colour 830/warm white (3000K), Colour rendering Ra=80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	29
Luminaire luminous flux (lm):	2500
lm/W:	88
Impact resistance (IK rating):	IK02 TA+25°C
Certifications:	IP 40, protection class I, BAP 65°<3000, Glow-wire flammability test 650°C, Impact resistance 0.20J, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2.4
Dimensions LxWxDxH (mm):	477 x 150
Cable entry KE X/Y (mm):	103 / 0
mounting method:	Surface single mounting, Wall surface-mounting
EAN-number:	4020863333981
Commodity code:	94051040

WBLR/500 LED 2500lm 830 • vw • ED • 25310144110



Lighting technology

Diffuser, opal-direct/indirect distribution
WBLR/500 LED 2500 lm 830



diffuser luminaire; Round luminaire housing made of deep-drawn sheet steel; Housing colour traffic white RAL 9016; Round domed acrylic glass diffuser, with opal matt smooth surface. Electrical connection via 3-pole connection terminal with plug-in contacts.

Dimensions LxWxDxH (mm): 477 x 150
Cable entry KE X/Y (mm): 103 / 0
Configuration: Lamps integrated: LED, Light colour 830/warm white (3000K), Colour rendering Ra=80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 2500
lm/W: 88
Operating device: Electronic driver (1 pcs.)
System performance (W): 29
Impact resistance (IK rating): IK02 TA+25°C
Certifications: IP 40, protection class I, BAP 65°<3000, Glow-wire flammability test 650°C, Impact resistance 0.20J, F, Indoor, CE

Regiolux GmbH
Type: WBLR/500 LED 2500 830 ET vw
Article number: 25310144110
Product deep link: <http://www.regiolux.de/en/article/25310144110>
5 year guarantee after registration on website.