Datasheet

REGIOLUX

Category (ETIM): Device mounts

Type: Device mount IP20-SDGLT LED

Order number: 18324574100

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver emergency light 3 hours (1 pcs.)

Mains voltage: 230V / 50Hz

System performance (W): 47
Ballast lumen factor BLF 9.1
(emergency lighting mode):

Luminaire luminous flux (lm): 7500 lm/W: 159

Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Colour of the housing: traffic white RAL 9016

Weight (net) (kg): 2.8

Dimensions LxWxH/DxH (mm): 1531 x 55 x 41


mounting method: Mounting rail system mounting

EAN-number: 4020863336128 Commodity code: 94051098

SDGLT LED 7500lm 840 • vw • EM pack 3h • 18324574100



Lighting technology Linear.Lens.Profil-direct narrow distribution SDGLT LED 7500 lm 840



 $\begin{array}{lll} \eta LB & 100 \ \% \\ Im/W & 159 \\ \Phi \downarrow / \uparrow & 99 \ \% \ / \ 1 \ \% \\ UGR \ q/I & 20.8 \ / \ 28.3 \end{array}$



Quick-fit mounting system Device mounts; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated lateral lever locks. LED unit in housing length for optically seamless light run. Housing colour traffic white RAL 9016; Direct narrow light distribution using Linear.Lens.Profil made of clear PMMA plastic. Optically seamless light run. With 3 hours emergency lighting battery and integrated status indicator; 3 hours emergency lighting operation. Heat-resistant cables including permanently fixed, 4-pole quick-mounting plug connector with tool-less phase preselection and locating finger; one wire from the through-wiring can be used as unswitched charging phase using an additional pole on the plug connector;

Dimensions LxWxH/DxH (mm): 1531 x 55 x 41

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour

rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 7500

lm/W: 159

Operating device: Electronic driver emergency light 3 hours (1 pcs.)

System performance (W): 47

Ballast lumen factor BLF (emergency lighting mode): 9.1

Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Regiolux GmbH

Type: SDGLT LED 7500 840 NL-B3 vw

Article number: 18324574100

Product deep link: http://www.regiolux.de/de/article/18324574100

5 year guarantee after registration on website.