


Category (ETIM):	Mounted luminaire
Type:	procube-CUAX LED
Order number:	60401024160
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	34
Luminaire luminous flux (lm):	3200
lm/W:	96
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<1500, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2.586
Dimensions LxWxH/DxH (mm):	1179 x 109 x 54
Cable entry KE X/Y (mm):	0 / 33
mounting method:	Surface single mounting, Surface light run mounting, Mounting rail mounting, Suspended single mounting, Suspended / light run mounting
EAN-number:	4020863306558
Commodity code:	94051098

procube-CUAX/1200-1 LED 3200lm 840 • vw • ED • 60401024160



Lighting technology
Micro-parabolic louvre, silky matt-direct distribution
CUAX/1200-1 LED 3200 lm 840



Mounted luminaire; Sheet steel housing, compact rectangular cross section, installation height 40 mm; prepared for fixing of end faces or luminaire connectors made of steel. Housing colour traffic white RAL 9016; Direct light distribution using reflectivity-enhanced aluminium parabolic louvre, silk matt with low installation height cross blades, for workstations, °65 < 1000 cd/m² omnidirectional glare suppression according to the current DIN EN 12464-1 standard, self-engaging, louvre is optically seamless for light run mounting; Electrical connection via 3-pole connection terminal with plug-in contacts. Required accessories: please order end faces, connectors and through-wiring separately according to luminaire arrangements. Mounting on mounting rail possible. Required accessories are available on request.

Dimensions LxWxH/DxH (mm): 1179 x 109 x 54
Cable entry KE X/Y (mm): 0 / 33
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 3200
lm/W: 96
Operating device: Electronic driver (1 pcs.)
System performance (W): 34
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<1500, F, Indoor, CE

Regiolux GmbH
Type: procube-CUAX/1200-1 LED 3200 840 ET vw
Article number: 60401024160
Product deep link: <http://www.regiolux.de/en/article/60401024160>
5 year guarantee after registration on website.

