


|                               |  |
|-------------------------------|--|
| Category (ETIM):              | Furniture luminaire/mirror luminaire   |
| Type:                         | SLG LED  |
| Order number:                 | 16161644125  |
| Configuration:                | Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10 |
| Operating device:             | Electronic driver (1 pcs.)   |
| Mains voltage:                | 230V / 50Hz  |
| System performance (W):       | 9  |
| Luminaire luminous flux (lm): | 1000   |
| lm/W:                         | 109  |
| Energy efficiency class:      | A+   |
| Certifications:               | IP 44, protection class I, Glow-wire flammability test 850°C, F, MM, Indoor, CE  |
| Colour of the housing:        | aluminium natural anodized   |
| Weight (net) (kg):            | 0.9  |
| Dimensions LxWxH/DxH (mm):    | 600 x 47 x 82  |
| Cable entry KE X/Y (mm):      | 150 / 0  |
| mounting method:              | Wall surface-mounting, Mounting on furniture   |
| EAN-number:                   | 4020863321865  |
| Commodity code:               | 94051098   |


**smile-SLG/0600 LED 1000lm 840 • aen • ED • 16161644125**



**Lighting technology**  
Diffuser, opal-direct/indirect distribution  
SLG/0600 LED 1000 lm 840



ηLB 100 %  
lm/W 109  
Φ ↓/↑ 77 % / 23 %



Furniture luminaire/mirror luminaire; Housing made of anodised extruded aluminium profile, screw fixable end faces made of plastic coated white aluminium (RAL 9006), vertical or horizontal wall mounting possible, with integrated cable duct and protection rated cable entry. Housing colour aluminium natural anodized; Direct/indirect light distribution using opal diffuser made of polycarbonate with smooth surface; Electrical connection via 3-pole connection terminal with plug-in contacts.

Dimensions LxWxH/DxH (mm): 600 x 47 x 82  
Cable entry KE X/Y (mm): 150 / 0  
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10  
Luminaire luminous flux (lm): 1000  
lm/W: 109  
Operating device: Electronic driver (1 pcs.)  
System performance (W): 9  
Energy efficiency class: A+  
Certifications: IP 44, protection class I, Glow-wire flammability test 850°C, F, MM, Indoor, CE

Regiolux GmbH  
Type: smile-SLG/0600 LED 1000 840 ET aen  
Article number: 16161644125  
Product deep link: <http://www.regiolux.de/en/article/16161644125>  
5 year guarantee after registration on website.

