

Datasheet


REGIOLUX

Category (ETIM):	Suspended luminaire
Type:	hokal-HLHX LED
Order number:	60533024160
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	42
Luminaire luminous flux (lm):	4000
lm/W:	96
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<1500, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	3.387
Dimensions LxWxDxH (mm):	1476 x 85 x 72
mounting method:	Suspended single mounting, Suspended / light run mounting
EAN-number:	4020863306756
Commodity code:	94051098


hokal-HLHX/1500 LED 4000lm 840 • vw • ED • 60533024160



Lighting technology
Micro-parabolic louvre, silky matt-direct distribution
HLHX/1500 LED 4000 lm 840



ηLB	100 %
lm/W	96
Φ ↓/↑	100 % / 0 %
UGR q/l	20.7 / 19.9
BAP	65° < 1500cd/m²



Suspended luminaire; Sheet steel housing with square design; prepared for fixing end faces or luminaire connectors made of steel; Housing colour traffic white RAL 9016; Direct light distribution using reflectivity-enhanced aluminium parabolic louvre, silk matt with low installation height cross blades, for workstations, °65 < 1500 cd/m² omnidirectional glare suppression according to the current DIN EN 12464-1 standard, self-engaging, louvre is optically seamless for light run mounting; Electrical connection via 3-pole connection terminal with plug-in contacts. Required accessories: order end faces, connectors, through-wiring and Y-wire-rope suspensions SAY-KS/SAYE-KL with 2000 mm suspension length separately according to luminaire arrangements.

Dimensions LxWxDxH (mm): 1476 x 85 x 72
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 4000
lm/W: 96
Operating device: Electronic driver (1 pcs.)
System performance (W): 42
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<1500, F, Indoor, CE

Regiolux GmbH
Type: hokal-HLHX/1500 LED 4000 840 ET vw
Article number: 60533024160
Product deep link: <http://www.regiolux.de/en/article/60533024160>
5 year guarantee after registration on website.

