


Category (ETIM):	Sports hall luminaire
Type:	THLA LED
Order number:	68130024100
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra=80; LED service life 50000h L80/B10
Operating device:	Electronic driver (2 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	86
Luminaire luminous flux (lm):	9700
lm/W:	114
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<3000, F, Tennis ball impact resistance, Protection against flying balls, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	20.26
Dimensions LxWxDxH (mm):	1548 x 484 x 90
Cable entry KE X/Y (mm):	0 / 70
mounting method:	Surface single mounting, Surface light run mounting, Mounting rail mounting, Suspended single mounting, Suspended / light run mounting
EAN-number:	4020863281466
Commodity code:	94051098


**THLA/1500-3 -2 LED 9700lm 840 • vw • ED  
• 68130024100**



**Lighting technology**  
Louvre, white-direct wide distribution  
THLA/1500-3 -2 LED 9700 lm 840



ηLB	100 %
lm/W	114
Φ ↓/↑	100 % / 0 %
UGR q/l	17.8 / 18.1
BAP	65° < 3000cd/m²



Sports hall luminaire; Sheet steel housing Housing colour traffic white RAL 9016; Direct wide-beam light distribution using sheet steel metal louvre with robust smooth cross blades; painted white similar to RAL 9016; with V reflector, can be folded down on one side; ball-proof. Louvre fastening using ball-proof spring catches that can only be opened with tools; fitted with 1x Regiolux LED unit, neutral white light colour (840) with very good colour consistency and high colour rendering Ra>80; Wiring in two-group series possible; electrical connection via 5-pole connection terminal with plug-in contacts. The accessories for mounting rail or suspended mounting installation must be ordered separately.

Dimensions LxWxDxH (mm): 1548 x 484 x 90

Cable entry KE X/Y (mm): 0 / 70

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra=80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 9700

lm/W: 114

Operating device: Electronic driver (2 pcs.)

System performance (W): 86

Energy efficiency class: A+

Certifications: IP 20, protection class I, BAP 65°<3000, F, Tennis ball impact resistance, Protection against flying balls, Indoor, CE

Regiolux GmbH

Type: THLA/1500-3 -2 LED 9700 840 ET vw

Article number: 68130024100

Product deep link: <http://www.regiolux.de/en/article/68130024100>

5 year guarantee after registration on website.

