


Category (ETIM):	Suspended luminaire
Type:	stail-SHLXI LED
Order number:	60334024160
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	57
Luminaire luminous flux (lm):	6300
lm/W:	111
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<1000, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	4.811
Dimensions LxWxDxH (mm):	1540 x 198 x 37
mounting method:	Suspended single mounting, Suspended / light run mounting
EAN-number:	4020863322473
Commodity code:	94051098

stail-SHLXI/1500-2 LED 6300lm 840 • vw • ED • 60334024160




Lighting technology

Micro-parabolic louvre, silky matt-direct/indirect distribution
SHLXI/1500-2 LED 6300 lm 840



ηLB	100 %
lm/W	111
Φ ↓/↑	36 % / 64 %
UGR q/l	13.1 / 12.3
BAP	65° < 1000cd/m²



Suspended luminaire; Sheet steel housing, flat rectangular cross section, visible installation height 26 mm, steel end faces, prepared for light run installation; Housing colour traffic white RAL 9016; Direct/indirect light distribution using reflectivity-enhanced silk matt aluminium parabolic louvre with low installation height cross blades, for workstations, 65° < 1500 cd/m² omnidirectional glare suppression according to the current DIN EN 12464-1 standard, self-engaging; Electrical connection via 3-pole connection terminal with plug-in contacts. Required accessories: Y-wire suspension for/without electrical connection must be ordered separately. Recommended minimum pendant length 0.5 m.

Dimensions LxWxDxH (mm): 1540 x 198 x 37
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 6300
lm/W: 111
Operating device: Electronic driver (1 pcs.)
System performance (W): 57
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<1000, F, Indoor, CE

Regiolux GmbH
Type: stail-SHLXI/1500-2 LED 6300 840 ET vw
Article number: 60334024160
Product deep link: <http://www.regiolux.de/en/article/60334024160>
5 year guarantee after registration on website.

