


Category (ETIM):	Device mounts
Type:	Device mount IP20-SDGLT LED
Order number:	18324506600
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	47
Luminaire luminous flux (lm):	7500
lm/W:	159
Ambient temperatures:	10°C / 40°C
Certifications:	IP 20, protection class I, F, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	1.7
Dimensions LxWxH/DxH (mm):	1531 x 55 x 41
mounting method:	Mounting rail system mounting
EAN-number:	4020863336111
Commodity code:	94051098

SDGLT LED 7500lm 840 • vw • DALI • 18324506600



Lighting technology
Linear.Lens.Profil-direct narrow distribution
SDGLT LED 7500 lm 840



Quick-fit mounting system Device mounts; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated lateral lever locks. LED unit in housing length for optically seamless light run. Housing colour traffic white RAL 9016; Direct narrow light distribution using Linear.Lens.Profil made of clear PMMA plastic. Optically seamless light run. Heat-resistant cables including fixed 5-pole rapid installation plug connector with tool-less phase pre-selection and locating finger.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 41
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 7500
lm/W: 159
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 47
Conditions: Suitable for use in ambient temperatures of 10°C to 40°C
Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGLT LED 7500 840 DALI vw
Article number: 18324506600
Product deep link: <http://www.regiolux.de/de/article/18324506600>
5 year guarantee after registration on website.