Datasheet

REGIOLUX

Category (ETIM): Suspended luminaire
Type: visula-VSHIMP LED
Order number: 43221014175

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver (1 pcs.)

Mains voltage: 230V / 50Hz
System performance (W): 54
Luminaire luminous flux (Im): 4900
Im/W: 90
Energy efficiency class: A+

Certifications: IP 20, protection class I, BAP 65°<3000, F, Indoor, CE

Colour of the housing: aluminium natural anodized

Weight (net) (kg): 6.3


Dimensions LxWxH/DxH (mm): 1199 x 330 x 30

mounting method: Suspended single mounting


EAN-number: 4020863304363 Commodity code: 94051098 visula-VSHIMP/1200 LED 4900lm 840 • aen • ED • 43221014175




Lighting technology
Diffuser, micro-prismatic-direct/indirect distribution
VSHIMP/1200 LED 4900 lm 840



 $\begin{array}{lll} \eta LB & 100~\% \\ Im/W & 90 \\ \Phi \downarrow / \uparrow & 84~\% / 16~\% \\ UGR~q/I & 18.1 / 18.2 \\ BAP & 65^\circ < 3000 cd/m^2 \end{array}$





Suspended luminaire; Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 30 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the bottom of the luminaire. Housing colour aluminium natural anodized; Direct/indirect light distribution, direct component using microprism made of PMMA, homogeneous light emission through lateral LED light coupling and overlying aluminium reflector with highly reflective white coating, with micro-perforation for the indirect light component; for workstations, omnidirectional glare suppression according to the current DIN-EN 12464-1 standard. Integrated LED driver design. Electrical connection via integrated transparent connection cable 3 x 0.75 mm², length 2300 mm, stripped cable ends. Suspension included

Dimensions LxWxH/DxH (mm): 1199 x 330 x 30

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 4900

Im/W: 90

Operating device: Electronic driver (1 pcs.)

System performance (W): 54 Energy efficiency class: A+

Certifications: IP 20, protection class I, BAP 65°<3000, F, Indoor, CE

Regiolux GmbH

Type: visula-VSHIMP/1200 LED 4900 840 ET aen

Article number: 43221014175

Product deep link: http://www.regiolux.de/en/article/43221014175

5 year guarantee after registration on website.