Datasheet

REGIOLUX

Category (ETIM): diffuser luminaire
Type: WQL LED
Order number: 25100014100

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver (1 pcs.)

Mains voltage: 230V / 50Hz
System performance (W): 13
Luminaire luminous flux (Im): 1400
Im/W: 106

Energy efficiency class: A+

Certifications: IP 65, protection class I, F, D, Indoor, CE

Colour of the housing: traffic white RAL 9016

Weight (net) (kg): 1.52

Dimensions LxWxH/DxH (mm): 300 x 300 x 83 Cable entry KE X/Y (mm): 115 / 30


mounting method: Surface single mounting, Wall surface-mounting

EAN-number: 4020863263455 Commodity code: 94051040

WQL LED 1400lm 840 • vw • ED • 25100014100



Lighting technologyDiffuser, opal-direct/indirect distribution
WQL LED 1400 lm 840



diffuser luminaire; Square diffuser luminaire made of recyclable polycarbonate with a very flat, slightly bevelled housing profile; Housing colour traffic white RAL 9016; Slightly bevelled, with corner stability, acrylic glass diffuser with opal, smooth surface adapted to the housing form; Electrical connection via 3-pole connection terminal with plug-in contacts.

Dimensions LxWxH/DxH (mm): 300 x 300 x 83

Cable entry KE X/Y (mm): 115 / 30

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour

rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 1400

Im/W: 106

Operating device: Electronic driver (1 pcs.)

System performance (W): 13 Energy efficiency class: A+

Certifications: IP 65, protection class I, F, D, Indoor, CE

Regiolux GmbH

Type: WQL LED 1400 840 ET vw Article number: 25100014100

Product deep link: http://www.regiolux.de/en/article/25100014100

5 year guarantee after registration on website.