

|                               |                                                                                                                        |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Category (ETIM):              | Mounted luminaire                                                                                                      |
| Type:                         | visula-VSAIG LED                                                                                                       |
| Order number:                 | 43351026615                                                                                                            |
| Configuration:                | Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10 |
| Operating device:             | Electronic driver DALI (1 pcs.)                                                                                        |
| Mains voltage:                | 230V / 50Hz                                                                                                            |
| System performance (W):       | 67                                                                                                                     |
| Luminaire luminous flux (lm): | 6100                                                                                                                   |
| lm/W:                         | 91                                                                                                                     |
| Energy efficiency class:      | A+                                                                                                                     |
| Certifications:               | IP 20, protection class I, F, Indoor, CE                                                                               |
| Colour of the housing:        | aluminium natural anodized                                                                                             |
| Weight (net) (kg):            | 9.1                                                                                                                    |
| Dimensions LxWxH/DxH (mm):    | 1480 x 330 x 42                                                                                                        |
| Cable entry KE X/Y (mm):      | 0 / 0                                                                                                                  |
| mounting method:              | Surface single mounting                                                                                                |
| EAN-number:                   | 4020863307036                                                                                                          |
| Commodity code:               | 94051098                                                                                                               |


**visula-VSAIG/1500 LED 6100lm 840 • aen • DALI • 43351026615**




## Lighting technology

Diffuser, frosted-direct/indirect distribution for ceiling lighting

VSAIG/1500 LED 6100 lm 840



|         |             |
|---------|-------------|
| ηLB     | 100 %       |
| lm/W    | 91          |
| Φ ↓/↑   | 84 % / 16 % |
| UGR q/l | 20.1 / 20.0 |



Mounted luminaire; Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 30 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the bottom of the luminaire. Housing colour aluminium natural anodized; Light distribution direct/indirect distribution, direct component using frosted pane made of PMMA, homogeneous light emission by lateral LED light coupling and fitted aluminium reflector in highly reflective white coating, with micro-perforation for a moderate ceiling illumination. Integrated LED driver design. Electrical connection and connection of control cable using 5-pole connection terminal with plug-in contacts.

Dimensions LxWxH/DxH (mm): 1480 x 330 x 42

Cable entry KE X/Y (mm): 0 / 0

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 6100

lm/W: 91

Operating device: Electronic driver DALI (1 pcs.)

System performance (W): 67

Energy efficiency class: A+

Certifications: IP 20, protection class I, F, Indoor, CE

Regiolux GmbH

Type: visula-VSAIG/1500 LED 6100 840 DALI aen

Article number: 43351026615

Product deep link: <http://www.regiolux.de/en/article/43351026615>

5 year guarantee after registration on website.

