Datasheet

Mains voltage:

REGIOLUX

Category (ETIM): Device mount IP 54

Type: Device mount IP54-SDGSOH LED

Order number: 18640404100

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver (1 pcs.)

230V / 50Hz System performance (W): 75 Luminaire luminous flux (lm): 10000 129

Ambient temperatures: -20°C / 25°C

Certifications: IP 54, protection class I, BAP 65°<3000, F, D,

DIN10500/Food, Indoor, CE

Colour of the housing: traffic white RAL 9016

Weight (net) (kg):

Dimensions LxWxH/DxH (mm): 1531 x 55 x 37

mounting method: Mounting rail system mounting


EAN-number: 4020863326075 Commodity code: 94051098

SDGSOH LED 10000lm 840 • vw • ED • 18640404100



Lighting technology

Individual.Lens.Optic-direct extremely narrow distribution SDGSOH LED 10000 lm 840



ηLB 100 % lm/W Φ 1/↑ ÚĞR q/I BAP

129 99 % / 1 % 13.4 / 12.0 65° < 3000cd/m²

Quick-fit mounting system Device mount IP 54; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated pressure locks. Lighttechnical element with transparent seal, end faces made of plastic, all-round closed seal to mounting rail. Housing colour traffic white RAL 9016; Extremely direct narrow-beam light distribution with controlled rack lighting using individual. lens. optic made of PMMA plastic. Continuous optics. Uniform LED spacing, even across circuit boards. 3-row LED arrangement. Light direction components are easy to maintain due to smooth surface which is easily cleaned. Heat-resistant cables including fixed 3-pole rapid installation plug connector with tool-less phase pre-selection and locating finger.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 37

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour

rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 10000

Im/W: 129

Operating device: Electronic driver (1 pcs.)

System performance (W): 75

Conditions: Suitable for use in ambient temperatures of -20°C to 25°C

Certifications: IP 54, protection class I, BAP 65°<3000, F, D, DIN10500/Food, Indoor, CE

Regiolux GmbH

Type: SDGSOH LED 10000 840 ET vw

Article number: 18640404100

Product deep link: http://www.regiolux.de/de/article/18640404100

5 year guarantee after registration on website.