

Datasheet


REGIOLUX

Category (ETIM):	Mounted luminaire
Type:	procube-CUAX LED
Order number:	60404024160
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	86
Luminaire luminous flux (lm):	8100
lm/W:	94
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<1000, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	4.2
Dimensions LxWxH/DxH (mm):	1479 x 161 x 54
Cable entry KE X/Y (mm):	0 / 56
mounting method:	Surface single mounting, Surface light run mounting, Mounting rail mounting, Suspended single mounting, Suspended / light run mounting
EAN-number:	4020863309658
Commodity code:	94051098


procube-CUAX/1500-2 LED 8100lm 840 • vw • ED • 60404024160



Lighting technology
Micro-parabolic louvre, silky matt-direct distribution
CUAX/1500-2 LED 8100 lm 840



ηLB	100 %
lm/W	94
Φ ↓/↑	100 % / 0 %
UGR q/l	20.5 / 19.8
BAP	65° < 1000cd/m²



Mounted luminaire; Sheet steel housing, compact rectangular cross section, installation height 40 mm; prepared for fixing of end faces or luminaire connectors made of steel. Housing colour traffic white RAL 9016; Direct light distribution using reflectivity-enhanced aluminium parabolic louvre, silk matt with low installation height cross blades, for workstations, °65 < 1000 cd/m² omnidirectional glare suppression according to the current DIN EN 12464-1 standard, self-engaging, louvre is optically seamless for light run mounting; Electrical connection via 3-pole connection terminal with plug-in contacts. Required accessories: please order end faces, connectors and through-wiring separately according to luminaire arrangements. Mounting on mounting rail possible. Required accessories are available on request.

Dimensions LxWxH/DxH (mm): 1479 x 161 x 54
Cable entry KE X/Y (mm): 0 / 56
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 8100
lm/W: 94
Operating device: Electronic driver (1 pcs.)
System performance (W): 86
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<1000, F, Indoor, CE

Regiolux GmbH
Type: procube-CUAX/1500-2 LED 8100 840 ET vw
Article number: 60404024160
Product deep link: <http://www.regiolux.de/en/article/60404024160>
5 year guarantee after registration on website.

