


Category (ETIM):	Mounted luminaire
Type:	hokal-HLAG LED
Order number:	60501026680
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	28
Luminaire luminous flux (lm):	2500
lm/W:	87
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	3.1
Dimensions LxWxH/DxH (mm):	1176 x 85 x 75
Cable entry KE X/Y (mm):	0 / 0
mounting method:	Surface single mounting, Surface light run mounting, Mounting rail mounting, Suspended single mounting, Suspended / light run mounting
EAN-number:	4020863318964
Commodity code:	94051098

hokal-HLAG/1200 LED 2500lm 840 • vw • DALI • 60501026680



Lighting technology
Diffuser, satined-direct distribution
HLAG/1200 LED 2500 lm 840



Mounted luminaire; Sheet steel housing with square design; prepared for fixing end faces or luminaire connectors made of steel; Housing colour traffic white RAL 9016; Direct light distribution; glare suppression using diffuse distribution frosted polycarbonate profile; diffuser is optically seamless for light run mounting; Electrical connection via 5-pole connection terminal with plug-in contacts. Required accessories: Please order end faces, connectors and through-wiring separately according to luminaire arrangements. Mounting on mounting rail possible. Required accessories are available on request.

Dimensions LxWxH/DxH (mm): 1176 x 85 x 75
Cable entry KE X/Y (mm): 0 / 0
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 2500
lm/W: 87
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 28
Energy efficiency class: A+
Certifications: IP 20, protection class I, F, Indoor, CE

Regiolux GmbH
Type: hokal-HLAG/1200 LED 2500 840 DALI vw
Article number: 60501026680
Product deep link: <http://www.regiolux.de/en/article/60501026680>
5 year guarantee after registration on website.

