


Category (ETIM):	Mounted luminaire
Type:	cubus-RSAXC LED
Order number:	65040014160
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra=80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	24
Luminaire luminous flux (lm):	3200
lm/W:	133
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<1000, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	4.05
Dimensions LxWxH/DxH (mm):	1188 x 140 x 69
Cable entry KE X/Y (mm):	80 / 41
mounting method:	Surface single mounting, Surface light run mounting, Mounting rail mounting
EAN-number:	4020863281053
Commodity code:	94051098


cubus-RSAXC-1200 LED 3200lm 840 • vw • ED • 65040014160



Lighting technology
Parabolic louvre, silky matt-direct distribution
RSAXC-1200 LED 3200 lm 840



ηLB	100 %
lm/W	133
Φ ↓/↑	100 % / 0 %
UGR q/l	15.5 / 19.0
BAP	65° < 1000cd/m²



Mounted luminaire; Sheet steel housing, rectangular cross-section, plastic end faces with integrated light run connectors; Housing colour traffic white RAL 9016; Direct light distribution using reflectivity-enhanced parabolic aluminium louvre, silk matt anodised, for workstations, 65°<1000 cd/m² omnidirectional glare suppression according to the current DIN EN 12464-1 standard, self-engaging, can be folded down on both sides; louvre is optically seamless for light run mounting. Neutral white light colour (840) with very good colour consistency and high colour rendering Ra=80; Electrical connection via 3-pole connection terminal with plug-in contacts. Mounting on mounting rail possible. Required accessories are available on request.

Dimensions LxWxH/DxH (mm): 1188 x 140 x 69
Cable entry KE X/Y (mm): 80 / 41
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra=80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 3200
lm/W: 133
Operating device: Electronic driver (1 pcs.)
System performance (W): 24
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<1000, F, Indoor, CE

Regiolux GmbH
Type: cubus-RSAXC-1200 LED 3200 840 ET vw
Article number: 65040014160
Product deep link: <http://www.regiolux.de/en/article/65040014160>
5 year guarantee after registration on website.

