


Category (ETIM):	Suspended luminaire
Type:	alvia-ALIMPR LED
Order number:	42162516670
Configuration:	Lamps integrated: LED, Light colour 830/warm white+830/warm white (3000K+3000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	62
Luminaire luminous flux (lm):	7900
lm/W:	127
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<3000, F, Indoor, CE
Colour of the housing:	aluminium natural anodized
Weight (net) (kg):	5.4
Dimensions LxWxDxH (mm):	1394 x 309 x 41
mounting method:	Suspended single mounting
EAN-number:	4020863289646
Commodity code:	94051098

alvia-ALIMPR/1400 LED 7900lm 830/830 • aen • DALI • 42162516670




Lighting technology

Diffuser, micro-prismatic-direct/indirect distribution
ALIMPR/1400 LED 7900 lm 830/830



Suspended luminaire; Extremely flat luminaire housing, made by BUSSE Design+Engineering GmbH, extruded aluminium profile, natural anodised, visible installation height 23 mm; rounded natural anodised aluminium end faces, high stability due to cross braces made of stainless steel; Housing colour aluminium natural anodized; Direct/indirect light distribution, direct component using micro-prismatic diffuser made of PMMA, indirect component and longitudinally structured and luminous sides via cover made of frosted polycarbonate foil as dust protection, high luminous flux with direct and indirect component in lumen ratio 2:1; warm white light colour (830) in direct and indirect component with very good colour consistency and high colour rendering Ra > 80; for workstations, 65° < 3000 cd/m² omnidirectional glare suppression according to current DIN EN 12464-1 standard; Two integrated DALI LED drivers, dimmable separately for direct and indirect component via DALI protocol. Electrical connection via integrated transparent connection cable 5 x 0.75 mm², length 2,300 mm, stripped cable ends. Suspension included. DALI controller must be ordered separately.



Dimensions LxWxDxH (mm): 1394 x 309 x 41
Configuration: Lamps integrated: LED, Light colour 830/warm white+830/warm white (3000K+3000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 7900
lm/W: 127
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 62
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<3000, F, Indoor, CE

Regiolux GmbH
Type: alvia-ALIMPR/1400 LED 7900 830/830 DALI aen
Article number: 42162516670
Product deep link: <http://www.regiolux.de/en/article/42162516670>
5 year guarantee after registration on website.