## **Datasheet**

## REGIOLUX

Category (ETIM): Device mounts

Type: Device mount IP20-SDGLB LED

Order number: 18314474100

Configuration: Lamps integrated: LED, Light colour 840/neutral white

(4000K), Colour rendering Ra>80; LED service life

50000h L80/B10

Operating device: Electronic driver emergency light 3 hours (1 pcs.)

Mains voltage: 230V / 50Hz System performance (W): 39

Ballast lumen factor BLF 11.8

(emergency lighting mode): Luminaire luminous flux (lm): 5

Luminaire luminous flux (lm): 5700 lm/W: 147

Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Colour of the housing: traffic white RAL 9016

Weight (net) (kg): 2.518

Dimensions LxWxH/DxH (mm): 1531 x 63 x 46


mounting method: Mounting rail system mounting

EAN-number: 4020863336883 Commodity code: 94051098

## SDGLB LED 5700lm 840 • vw • EM pack 3h • 18314474100



Lighting technology Linear.Lens.Profil-direct wide distribution SDGLB LED 5700 Im 840



ηLB 100 % Im/W 147 Φ ↓/↑ 99 % / 1 % UGR q/I 22.6 / 27.0

4

Quick-fit mounting system Device mounts; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated lateral lever locks. LED unit in housing length for optically seamless light run. Housing colour traffic white RAL 9016; Direct, wide light distribution using Linear.Lens.Profil made of matt PMMA plastic. Optically seamless light run. With 3 hours emergency lighting battery and integrated status indicator; 3 hours emergency lighting operation. Heat-resistant cables including permanently fixed, 4-pole (or dimmable versions: 6-pole) quick-mount plug connector with tool-less phase pre-selection and locating finger; one wire of the throughwiring can be used as unswitched charging phase using an additional pole on the plug connector:

Dimensions LxWxH/DxH (mm): 1531 x 63 x 46

Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour

rendering Ra>80; LED service life 50000h L80/B10

Luminaire luminous flux (lm): 5700

Im/W: 147

Operating device: Electronic driver emergency light 3 hours (1 pcs.)

System performance (W): 39

Ballast lumen factor BLF (emergency lighting mode): 11.8

Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Regiolux GmbH

Type: SDGLB LED 5700 840 NL-B3 vw

Article number: 18314474100

Product deep link: http://www.regiolux.de/de/article/18314474100

5 year guarantee after registration on website.