

Datasheet

REGIOLUX


Category (ETIM):	Suspended luminaire
Type:	stail-SHPI LED
Order number:	60312026690
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver DALI (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	36
Luminaire luminous flux (lm):	4100
lm/W:	114
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<3000, F, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	4.63
Dimensions LxWxDxH (mm):	1240 x 198 x 37
mounting method:	Suspended single mounting
EAN-number:	4020863309542
Commodity code:	94051098

stail-SHPI/1200-2 LED 4100lm 840 • vw • DALI • 60312026690




Lighting technology

Diffuser, micro-prismatic-direct/indirect distribution
SHPI/1200-2 LED 4100 lm 840



ηLB	100 %
lm/W	114
Φ ↓/↑	51 % / 49 %
UGR q/l	14.9 / 15.4
BAP	65° < 3000cd/m²



Suspended luminaire; Sheet steel housing, flat rectangular cross section, visible installation height 26 mm, steel end faces; Housing colour traffic white RAL 9016; Direct/indirect light distribution using micro prismatic glass, for workstations, 65° < 3000 cd/m² omnidirectional glare suppression according to current DIN-EN 12464-1 standard; Electrical connection via 5-pole translucent connection cable with wire end sleeves. Required accessories: Y-wire suspension for/without electrical connection must be ordered separately. Recommended pendulum length min. 0,5m.

Dimensions LxWxDxH (mm): 1240 x 198 x 37
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 4100
lm/W: 114
Operating device: Electronic driver DALI (1 pcs.)
System performance (W): 36
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<3000, F, Indoor, CE



Regiolux GmbH

Type: stail-SHPI/1200-2 LED 4100 840 DALI vw

Article number: 60312026690

Product deep link: <http://www.regiolux.de/en/article/60312026690>

5 year guarantee after registration on website.