


Category (ETIM):	Mounted luminaire
Type:	visula-VSAIMP LED
Order number:	43321014175
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	54
Luminaire luminous flux (lm):	4900
lm/W:	90
Energy efficiency class:	A+
Certifications:	IP 20, protection class I, BAP 65°<3000, F, Indoor, CE
Colour of the housing:	aluminium natural anodized
Weight (net) (kg):	7.5
Dimensions LxWxH/DxH (mm):	1199 x 330 x 42
Cable entry KE X/Y (mm):	0 / 0
mounting method:	Surface single mounting
EAN-number:	4020863305384
Commodity code:	94051098

visula-VSAIMP/1200 LED 4900lm 840 • aen
• ED • 43321014175




Lighting technology

Diffuser, micro-prismatic-direct/indirect distribution for ceiling lighting
VSAIMP/1200 LED 4900 lm 840



ηLB	100 %
lm/W	90
Φ ↓/↑	84 % / 16 %
UGR q/l	18.1 / 18.2
BAP	65° < 3000cd/m²



Mounted luminaire; Ultra-flat luminaire housing, extruded aluminium profile, naturally anodised, visible installation height 30 mm; end faces and side parts made of naturally anodised aluminium with continuous longitudinal groove, rounded towards the bottom of the luminaire. Housing colour aluminium natural anodized; Direct/indirect light distribution, direct portion by means of a microprism made of PMMA, homogeneous light emission through lateral LED light coupling and fitted aluminium reflector in a highly reflective white coating, with micro-perforation for a moderate ceiling illumination; for computer screen workstations, omnidirectional glare suppression according to the current norm DIN-EN 12464-1. Integrated LED driver design. Electrical connection via 3-pole connection terminal with plug-in contacts.



Dimensions LxWxH/DxH (mm): 1199 x 330 x 42
Cable entry KE X/Y (mm): 0 / 0
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 4900
lm/W: 90
Operating device: Electronic driver (1 pcs.)
System performance (W): 54
Energy efficiency class: A+
Certifications: IP 20, protection class I, BAP 65°<3000, F, Indoor, CE

Regiolux GmbH
Type: visula-VSAIMP/1200 LED 4900 840 ET aen
Article number: 43321014175
Product deep link: <http://www.regiolux.de/en/article/43321014175>
5 year guarantee after registration on website.