


Category (ETIM):	Device mounts
Type:	Device mount IP20-SDGLK LED
Order number:	18230404100
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	40
Luminaire luminous flux (lm):	5500
lm/W:	138
Energy efficiency class:	A++
Ambient temperatures:	10°C / 35°C
Certifications:	IP 20, protection class I, F, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2
Dimensions LxWxH/DxH (mm):	1531 x 63 x 54
mounting method:	Mounting rail system mounting
EAN-number:	4020863302017
Commodity code:	94051098


SDGLK LED 5500lm 840 • vw • ED • 18230404100



Lighting technology
Diffuser, frosted-direct/indirect distribution
SDGLK LED 5500 lm 840



ηLB	100 %
lm/W	138
Φ ↓/↑	84 % / 16 %
UGR q/l	24.2 / 22.8



Quick-fit mounting system Device mounts; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated lateral lever locks. LED unit in housing length for optically seamless light run. Housing colour traffic white RAL 9016; Direct/indirect light distribution, frosted diffuser made of PMMA plastic with inner longitudinal prisms. Optically seamless light run. Heat-resistant cables including fixed 3-pole rapid installation plug connector with tool-free phase preselection and locating finger.

Dimensions LxWxH/DxH (mm): 1531 x 63 x 54
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 5500
lm/W: 138
Operating device: Electronic driver (1 pcs.)
System performance (W): 40
Energy efficiency class: A++
Conditions: Suitable for use in ambient temperatures of 10°C to 35°C
Certifications: IP 20, protection class I, F, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGLK LED 5500 840 ET vw
Article number: 18230404100
Product deep link: <http://www.regiolux.de/de/article/18230404100>
5 year guarantee after registration on website.