

Datasheet

REGIOLUX

Category (ETIM):	Control unit+sensor
Type:	DALI signal, Switch signal Compact control devices, Switching control devices-LC-BEG PD4-S-DE
Order number:	84506014100
Mains voltage:	230V / 50Hz
Certifications:	IP 20, protection class II, Indoor, CE
Weight (net) (kg):	0.1
Dimensions LxWxH/DxH (mm):	97 x 103
mounting method:	Ceiling recessing single mounting
EAN-number:	4020863291564
Commodity code:	85365080

LC-BEG PD4-S-DE • 84506014100



Presence slave sensor for ceiling recessing

Presence sensor, slave sensor with circular and long-range monitoring area, surface mounting, for master/slave combination. Only one master for light switching necessary; motion detection in all room segments possible with slave sensors; switching pulse to the master in the case of detected movement; recognition of the motion independent of ambient brightness; sensor and power part in the same housing; range in sitting position Ø6.4 m, lateral Ø24.0 m, frontal Ø8.0 m. A master sensor (LC-BEG PD4-M-DALI-DE) for the operation of the control is also required. Optional wire basket and cover strips.

Dimensions LxWxH/DxH (mm): 97 x 103

Certifications: IP 20, protection class II, Indoor, CE

Regiolux GmbH

Type: LC-BEG PD4-S-DE

Article number: 84506014100

Product deep link: <http://www.regiolux.de/de/article/84506014100>