


Category (ETIM):	Device mounts
Type:	Device mount IP54-SDGS LED
Order number:	18462074100
Configuration:	Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Operating device:	Electronic driver emergency light 3 hours (1 pcs.)
Mains voltage:	230V / 50Hz
System performance (W):	52
Ballast lumen factor BLF (emergency lighting mode):	7.2
Luminaire luminous flux (lm):	7000
lm/W:	138
Energy efficiency class:	A+
Certifications:	IP 54, protection class I, F, D, DIN10500/Food, Indoor, CE
Colour of the housing:	traffic white RAL 9016
Weight (net) (kg):	2.7
Dimensions LxWxH/DxH (mm):	1531 x 55 x 43
mounting method:	Mounting rail system mounting
EAN-number:	4020863306817
Commodity code:	94051098


SDGS LED 7000lm 840 • vw • EM pack 3h • 18462074100



Lighting technology
open distribution-general diffuse
SDGS LED 7000 lm 840



ηLB	100 %
lm/W	138
Φ ↓/↑	100 % / 0 %
UGR q/l	27.7 / 28.8



Quick-fit mounting system Device mounts; Device mount made of galvanised, profiled sheet steel, surface coated with polyester resin enamel. Toolless fastening with two integrated rotary catches. LED unit made of naturally anodised extruded aluminium profile with end faces made of plastic. Suitable for the mounting of LED light directing components. End faces made of plastic, all-round closed seal to mounting rail. Housing colour traffic white RAL 9016; Direct, general diffuse light distribution. LED diffuser cover made of polycarbonate. With 3 hours emergency light battery and integrated status indicator; three hours emergency light operation. Heat-resistant cables including permanently fixed 4-pole quick-mount plug connector with tool-free phase preselection and locating finger; one wire of the through-wiring can be used as unswitched charging phase using additional pole on the plug connector; Can be combined with the self-supporting specular reflectors SDFA LED, SDFB LED, SDFT LED und SDFH LED.

Dimensions LxWxH/DxH (mm): 1531 x 55 x 43
Configuration: Lamps integrated: LED, Light colour 840/neutral white (4000K), Colour rendering Ra>80; LED service life 50000h L80/B10
Luminaire luminous flux (lm): 7000
lm/W: 138
Operating device: Electronic driver emergency light 3 hours (1 pcs.)
System performance (W): 52
Ballast lumen factor BLF (emergency lighting mode): 7.2
Energy efficiency class: A+
Certifications: IP 54, protection class I, F, D, DIN10500/Food, Indoor, CE

Regiolux GmbH
Type: SDGS LED 7000 840 NL-B3 vw
Article number: 18462074100
Product deep link: <http://www.regiolux.de/de/article/18462074100>
5 year guarantee after registration on website.