

Product name


202-DS5-145

Item number

34201

Manufacturer

ETHERMA



Product description

Heating mat for thin bed, 0.7m², 50x145cm, 150W, 230V

The DS mesh heating mat is a factory-made heating mat for temperature control of floors, heating rooms or insulating walls from the cold. Due to the 2.7 mm thin structure, the mesh heating mat enables a low floor height construction. The heating mat is self-adhesive and the dipole design guarantees easy installation in the tile adhesive bed - with a virtually magnetic field-free operation. Special processing guarantees 100% reliable, easy installation and high stability of the heating mat. Upon request, we are also happy to custom manufacture DS mesh heating mats with custom size, voltage, power and shape. Dipole heating conductor, low magnetic field, nominal temperature: up to 90°C, system design: according to VDE 0700, heating conductor thickness: 2.7 mm, protection rating: IP X7, grid: 12x12 mm, self-adhesive, CE marking, certification mark: VDE, protective measure: 30 mA RCD protection circuit, standard connection cable: 4 m, 2x1.0 mm² protective braiding.

Technical Details

Model	Other	Connection voltage	230 23 Volt 0
With support mat	Yes	Connected load	150 15 Watt 0
Fixation thermal conductor	Glued	Power	200 Watt per square metre
Self-adhesive	Yes	Heating conductor load	10 Watt per metre
Suitable for damp space	Yes	Resistance	353 Ohm
Suitable as outdoor surface heating	No	Number of cold conductors	1
Suitable as roof surface heating	No	Length of cold conductors	3000 Millimetre
With controller	No	Surface	0.7 Square metre
With room temperature controller	No	Length	1450 Millimetre
With floor temperature sensor	No	Width	500 Millimetre
		Thickness	2.7 Millimetre