

## Product name

ET-KRTV-19

## Item number

32890

## Manufacturer

ETHERMA



## Product description

Capillary tube thermostat for room heating, knob outside

Capillary tube thermostat for room temperature control, temperature range: 5 to 60 °C, voltage: 230/400 V, switching current: 16/6A, protection rating: IP 55.

## Technical Details

|                                         |                            |                                               |                      |
|-----------------------------------------|----------------------------|-----------------------------------------------|----------------------|
| <b>Model</b>                            | On/Off                     | <b>Measuring range</b>                        | 0 40 Degrees celsius |
| <b>Type of power supply</b>             | 230 V AC                   | <b>Number of heater outputs</b>               | 1                    |
| <b>Connection</b>                       | 2-wire                     | <b>Number of cooler outputs</b>               | 1                    |
| <b>With receiver</b>                    | No                         | <b>Differential value</b>                     | 1 1 Kelvin           |
| <b>External sensor</b>                  | No                         | <b>Number of modules (module system)</b>      | 0                    |
| <b>Thermal feedback</b>                 | Series                     | <b>Max. contact voltage</b>                   | 400 Volt             |
| <b>Control characteristic</b>           | P                          | <b>Max. contact load</b>                      | 16 Ampere            |
| <b>Suitable for heating</b>             | Yes                        | <b>RAL-number</b>                             | 0                    |
| <b>Suitable for cooling</b>             | No                         | <b>Height</b>                                 | 110 Millimetre       |
| <b>Adjustable differential</b>          | No                         | <b>Width</b>                                  | 75 Millimetre        |
| <b>Temperature readable</b>             | No                         | <b>Depth</b>                                  | 69 Millimetre        |
| <b>With sound indicator</b>             | No                         | <b>Diameter</b>                               | 0 Millimetre         |
| <b>Sensor/feeler type</b>               | Bimetal                    | <b>Standby power consumption (solstandby)</b> | 0 Watt               |
| <b>Mounting method</b>                  | Surface mounted            |                                               |                      |
| <b>With display</b>                     | No                         |                                               |                      |
| <b>Operation</b>                        | Turn                       |                                               |                      |
| <b>Concealed operation</b>              | No                         |                                               |                      |
| <b>With tap water circuit</b>           | No                         |                                               |                      |
| <b>Contact type</b>                     | Normally open contact (NO) |                                               |                      |
| <b>Degree of protection (IP)</b>        | IP55                       |                                               |                      |
| <b>Degree of protection (NEMA)</b>      | Other                      |                                               |                      |
| <b>Explosion-proof</b>                  | No                         |                                               |                      |
| <b>Colour</b>                           | Grey                       |                                               |                      |
| <b>Class of the temperature control</b> | II                         |                                               |                      |
| <b>Compatible with Apple HomeKit</b>    | No                         |                                               |                      |

## DATASHEET.

---

|                                         |    |
|-----------------------------------------|----|
| <b>Compatible with Google Assistant</b> | No |
| <b>Compatible with Amazon Alexa</b>     | No |
| <b>IFTTT support available</b>          | No |