

Product name


NHM-WSST-0-2

Item number

40690

Manufacturer

ETHERMA



Product description

Wall heating made to measure, up to 2m², up to 300W/m²

This custom-made mesh heating mat is a factory-made heating mat, which guarantees a technically correct solution for wall heating. The heating mats are sized and produced according to the application. The outputs vary between 10 and 300 W/m² depending on the heat-sealing band. As voltage, the following can be realized: 12, 24, 48, 120, 230 and 400 V. Applications range from custom mats in bathroom walls or tiled showers, heating booths, for cold insulation and mold prevention. An ETHERMA technician will be happy to help with project planning and implementation. Dipole heating conductor, low magnetic field, outer and inner Teflon layer, nominal temperature: 90 °C, system design: according to VDE 0700, heating conductor thickness: 3.3 mm, protection rating: IP X7, mains grid: 12x12 mm, CE marking, protective measure: RCD 30 mA, connection cable: 4 m, 2x1.0(1.5) mm² protective braiding, 12-400 V.

Technical Details

Model	Heating cable	Connection voltage	24 230 Volt
With support mat	Yes	Connected load	300 60 Watt 0
Fixation thermal conductor	Sewed	Power	300 Watt per square metre
Self-adhesive	Yes	Heating conductor load	15 Watt per metre
Suitable for damp space	Yes	Resistance	0 Ohm
Suitable as outdoor surface heating	No	Number of cold conductors	1
Suitable as roof surface heating	Yes	Length of cold conductors	4000 Millimetre
With controller	No	Surface	1 Square metre
With room temperature controller	No	Length	0 Millimetre
With floor temperature sensor	No	Width	0 Millimetre
		Thickness	3.3 Millimetre