

## Product name

ET-AQUA-WHM-3

## Item number

41103

## Manufacturer

ETHERMA



## Product description

Hydraulic instantaneous water heater, 3.5kW, 230V

The hydraulic instantaneous water heater ET-AQUA-WHM, has a pressure-resistant design and is suitable for processing hot water quickly for sinks with limited water volume. Due to a built-in differential pressure switch, the device automatically switches on the heating mode. Water pressure: 1.2 to 6.0 bar, for wall mounting, Colour: White, Protection rating: IP 24, Water connection: Gz 3/8", 230 V.

## Technical Details

|                                        |                      |                                           |                  |
|----------------------------------------|----------------------|-------------------------------------------|------------------|
| <b>Material pressure tank</b>          | Plastic              | <b>Nominal content</b>                    | 1.7 Litre        |
| <b>Suitable for KNX</b>                | No                   | <b>Max. allowable operating pressure</b>  | 6 Bar            |
| <b>Operation</b>                       | Manual               | <b>Nominal power</b>                      | 3.5 Kilowatt     |
| <b>Temperature indication</b>          | None                 | <b>Nominal voltage 1</b>                  | 230 Volt         |
| <b>With display</b>                    | No                   | <b>Nominal voltage 2</b>                  | 230 Volt         |
| <b>Mounting method</b>                 | Over sink/under sink | <b>Connected load</b>                     | 3.5 3.5 Kilowatt |
| <b>Power control</b>                   | Electronic           | <b>Outer pipe diameter cold tap water</b> | 12 Millimetre    |
| <b>Heating system</b>                  | Tube heating element | <b>Outer pipe diameter hot tap water</b>  | 12 Millimetre    |
| <b>Safety breaker</b>                  | Pressure switch-off  | <b>Height</b>                             | 225 Millimetre   |
| <b>Degree of protection (IP)</b>       | IP24                 | <b>Width</b>                              | 168 Millimetre   |
| <b>Cold tap water connection</b>       | External thread      | <b>Depth</b>                              | 76 Millimetre    |
| <b>Nominal diameter cold tap water</b> | 3/8 inch (10)        | <b>Weight</b>                             | 1.2 Kilogram     |
| <b>Hot tap water connection</b>        | External thread      |                                           |                  |
| <b>Nominal diameter hot tap water</b>  | 3/8 inch (10)        |                                           |                  |
| <b>Suitable for plastic tube</b>       | Yes                  |                                           |                  |
| <b>Suitable for preheated water</b>    | Yes                  |                                           |                  |
| <b>Type of regulation</b>              | Hydraulic            |                                           |                  |
| <b>With tap/mixer</b>                  | No                   |                                           |                  |
| <b>Energy efficiency class</b>         | A                    |                                           |                  |