

Nom du produit

Stapaflex-FPR

Numéro de l'article

30011

Fabricant

ETHERMA

**Description du produit**

Tuyau d'installation Stapaflex asphalte DN 20

Tuyau d'installation blindé pour la pose de capteurs et de lignes de raccordement dans les surfaces en asphalte. Le tuyau résiste aux températures élevées lors de l'application de chaussées en asphalte.

Détails techniques

Material	Aluminium	Inner diameter	16 Millimetre
Material quality	Other	Outer diameter	20 Millimetre
Surface protection	Untreated	Operating temperature	220 220 Degrees celsius
Quality of surface coating	Other		
Surface polished	No		
Surface brushed	No		
Model	Pliable corrugated		
Connection 1	Other		
Connection 2	Other		
Colour	Grey		
Flush-mounted installation	Yes		
Surface mounting	No		
Suitable for concrete installation	Yes		
Machine and systems installation	Yes		
Suitable for underfloor installation (bitumen, hot asphalt)	Yes		
Suitable for underfloor installation (screed)	Yes		
Outdoor installation	Yes		
Installation on wood	Yes		
Suitable for hollow wall installation	Yes		
Suitable for underground installation	Yes		
Compressive strength class	Medium (class 3, 750 N)		

