

Nom du produit

ET-3356-20

Numéro de l'article

40769

Fabricant

ETHERMA

**Description du produit**

Capteur d'humidité et de température pour ET-9300/ET-9200F, L 20m

L'ET-3356-20 est un capteur de sol pour la double mesure de la température et de l'humidité des revêtements routiers carrossables ou piétonniers. Il s'agit d'un modèle robuste en laiton, entièrement encastré. Grâce à sa très faible hauteur, il est particulièrement adapté aux escaliers, aux terrasses, etc. Le câble de raccordement peut être installé au choix dessous ou sur le côté. Incl. gaine et câble de raccordement 20 m. Diamètre 68 mm, H 31 mm (câble de côté) ou 65 mm (câble dessous), Charge admise 20 kN, Plage de températures -30 °C à °C, Mesure de l'humidité -20 °C à °C.

Détails techniques

Scope of application	Outside	Cable length	20 Metre
With mounting material	No	Sensor length	0 Millimetre
Suitable for wall mounting	No	Insert length	0 Millimetre
Suitable for ceiling mounting	No	Diameter sensor element	0 Millimetre
Suitable for duct mounting	No	Number of measuring points	1
Suitable for tube mounting	No	CO2 measuring range	0 0 parts per million
Suitable for air	Yes	VOC measuring range	0 0 parts per million
Suitable for liquids	Yes	Temperature measuring range	75 75 Degrees celsius
Suitable for gases	No	Measuring range relative air humidity	0 1 Percentage
With housing	Yes	Measuring range absolute air humidity	0 0 Gram per cubic metre
Cover attachment	Other	Enthalpy measuring range	0 0 Kilojoule per kilogram
Sensor element inside housing	Yes	Dewpoint measuring range	0 0 Percentage
Sensor element outside housing	No	Particulate matter measuring range (PM)	0 0 Microgram per cubic metre
Fixed cable to sensor	Yes	Number of measuring ranges	0
Material element	Other	Tolerance	5 Percentage
Technology	Other	Rated supply voltage AC	0 0 Volt
Active temperature measurement	Yes	Rated supply voltage DC	12 12 Volt
Passive temperature measurement	No	Number of output signals	1

Average temperature measuring	No	Number of output ranges 0 V ... 5 V	0
Measurement of CO2	No	Number of output ranges 0 V ... 10 V	0
Measurement of VOC	No	Number of output ranges 2 V ... 10 V	0
Measurement of relative air humidity	Yes	Number of output ranges 0 mA ... 20 mA	0
Measurement of absolute air humidity	No	Number of output ranges 4 mA ... 20 mA	0
Enthalpy measurement	No	Scope of application, flow speed medium	0 0 Metre per second
Measurement of dewpoint	No	Max. ambient humidity (non-condensing)	10 Percentage 0
Particulate matter measurement (PM)	No	Ambient temperature	75 Degrees celsius 75
Offset setting possible	No	Housing height	35 Millimetre
Trend representation	No	Housing width	70 Millimetre
Error registration possible	No	Housing depth	70 Millimetre
Sensor type	PTC		
Potentiometer with adjustment knob	No		
Supporting protocol for BACnet	No		
Supporting protocol for Modbus	No		
Supporting protocol for MP (multi point)	No		
Supporting protocol for KNX	No		
LoRa technology	No		
NFC (Near Field Communication)	No		
Bluetooth	No		
Wi-Fi-compatible	No		
Standby push button	No		
Wireless	No		
With display	No		
Type of display	Other		
Type of power supply	Power cord		
Type of electric connection	Other		
With reverse polarity protection	No		
Explosion-proof	No		
Degree of protection (IP)	IP67		
Housing colour	Other		
UV resistant	Yes		
Compatible with Apple HomeKit	No		
Compatible with Google Assistant	No		
Compatible with Amazon Alexa	No		
IFTTT support available	No		