

## Product name

LAVA2-GLAS-750-PW

## Item number

39628

## Manufacturer

ETHERMA



## Product description

infrared heating panel, glass, pure white, 130x63cm, 750W, 230V

LAVA 2.0 design infrared heating panels work particularly efficiently and save energy. The 6 mm thick surface material made of safety glass, special ceramic or fine stone, as well as 2 temperature limiters in all panels ensure safety at all times. The innovative technology makes the surfaces a very good radiation emitter. In combination with the even heat distribution on the surface, the optimally insulated back surface guarantees a high radiation efficiency and thus maximum infrared heat radiation to the front into the room. The frame-less design is modern. There are four surfaces (STEEL/GLASS/CERAMIC/STONE) and up to 6 power settings to choose from. The practical Plug & Play box at the back of all LAVA 2.0 models allows easy installation of a control, whether directly on the unit, by radio or by means of a wired controller. With LAVA DYL 2.0 - Design Your LAVA - it is possible to apply your own designs, pictures and photos on the LAVA GLAS 2.0 or LAVA BATH 2.0. On/off switch, surface temperature: max. 95 °C, vertical and horizontal wall mount possible, protection rating: IP X4, surfaces: sheet steel, 6 mm toughened safety glass, 6 mm special ceramic or 6 mm fine stone, plug connection cable: 1 m, certification mark: TÜV, CE marking.

## Technical Details

|                                           |                     |                                 |                    |
|-------------------------------------------|---------------------|---------------------------------|--------------------|
| <b>Type of IR radiation</b>               | IR-C                | <b>Power consumption</b>        | 750 Watt           |
| <b>Mounting method</b>                    | Surface mounting    | <b>Supply voltage</b>           | 230 230 Volt       |
| <b>Mounting direction</b>                 | Horizontal/vertical | <b>Frequency supply voltage</b> | 50 50 Hertz        |
| <b>Ceiling mounting</b>                   | No                  | <b>Max. surface temperature</b> | 95 Degrees celsius |
| <b>Degree of protection (IP)</b>          | IPX4                | <b>Height</b>                   | 630 Millimetre     |
| <b>Colour</b>                             | White               | <b>Width</b>                    | 1300 Millimetre    |
| <b>With imprint</b>                       | No                  | <b>Depth</b>                    | 61 Millimetre      |
| <b>With room temperature controller</b>   | No                  | <b>RAL-number</b>               | 0                  |
| <b>With mounting material</b>             | Yes                 | <b>Colour temperature</b>       | 0 0 Kelvin         |
| <b>With framework</b>                     | No                  |                                 |                    |
| <b>Material framework</b>                 | Other               |                                 |                    |
| <b>Colour framework</b>                   | White               |                                 |                    |
| <b>Surface treatment</b>                  | Other               |                                 |                    |
| <b>Surface structure front side panel</b> | Smooth              |                                 |                    |
| <b>With lighting cove</b>                 | No                  |                                 |                    |
| <b>Dimmable</b>                           | No                  |                                 |                    |
| <b>Light outlet</b>                       | Direct              |                                 |                    |