

## Product name

LAVA2-GLAS-700-DYL

## Item number

39667

## Manufacturer

ETHERMA



## Product description

infrared heating panel with customer motif, glass, 160x63cm, 700W

The LAVA 2.0 DYL infrared heating panel offers the possibility of infrared heating panel customization. No matter whether a vacation photo or company logo, the customer pattern is applied. And here, you don't even notice that the pattern devices are in fact a contemporary infrared heating panel. The LAVA 2.0 DYL is suitable for wall mounting and can be mounted vertically or horizontally depending on the structure. The 6 mm safety glass and 2 temperature limiters ensure maximum safety at all times. The innovative technology makes the glass a very good radiation emitter. In combination with the even heat distribution on the surface, the optimally insulated back surface guarantees a high radiation efficiency and thus maximum infrared heat radiation to the front into the room. The frame-less design is modern. There are 4 options to choose from. The practical Plug & Play box at the back of all LAVA 2.0 models allows easy installation of a control, whether directly on the unit, by radio or by means of a wired controller. On/off switch, surface temperature: max. 70 °C, protection rating: IP X4, surfaces: 6 mm ESG safety glass, plug connection line: 1 m, TÜV, CE marking, 230 V.

## Technical Details

|                                           |                     |                                 |                    |
|-------------------------------------------|---------------------|---------------------------------|--------------------|
| <b>Type of IR radiation</b>               | IR-C                | <b>Power consumption</b>        | 700 Watt           |
| <b>Mounting method</b>                    | Surface mounting    | <b>Supply voltage</b>           | 230 230 Volt       |
| <b>Mounting direction</b>                 | Horizontal/vertical | <b>Frequency supply voltage</b> | 50 50 Hertz        |
| <b>Ceiling mounting</b>                   | No                  | <b>Max. surface temperature</b> | 70 Degrees celsius |
| <b>Degree of protection (IP)</b>          | IPX4                | <b>Height</b>                   | 630 Millimetre     |
| <b>Colour</b>                             | Multi-coloured      | <b>Width</b>                    | 1600 Millimetre    |
| <b>With imprint</b>                       | Yes                 | <b>Depth</b>                    | 61 Millimetre      |
| <b>With room temperature controller</b>   | No                  | <b>RAL-number</b>               | 0                  |
| <b>With mounting material</b>             | Yes                 | <b>Colour temperature</b>       | 0 0 Kelvin         |
| <b>With framework</b>                     | No                  |                                 |                    |
| <b>Material framework</b>                 | Other               |                                 |                    |
| <b>Colour framework</b>                   | Other               |                                 |                    |
| <b>Surface treatment</b>                  | Other               |                                 |                    |
| <b>Surface structure front side panel</b> | Smooth              |                                 |                    |
| <b>With lighting cove</b>                 | No                  |                                 |                    |
| <b>Dimmable</b>                           | No                  |                                 |                    |
| <b>Light outlet</b>                       | Direct              |                                 |                    |