

## Product name

LAVABATH2-GL-600-PW

## Item number

38087

## Manufacturer

ETHERMA



## Product description

Bathroom infrared heating panel glass pure white 160x50cm 500W 230V

The LAVA BATH 2.0 is the perfect heater for your bathroom. Strong surface material made of ESG safety glass, corian or fine stone, as well as 2 temperature limiters in all panels, ensure safety when in use at all times. The innovative technology makes the surfaces a very good radiation emitter. In conjunction with the even heat distribution on the surface, the optimally insulated back surface guarantees high radiation efficiency and thus maximum infrared heat radiation to the front of the room; once switched on, depending on the surface, the panel is heated to max. 80 °C and provides comforting warmth within a couple of moments. And, thanks to its included towel holder, it also ensures cozy, warm towels. The frame-less design is modern. There are four surfaces (STEEL/GLASS/STONE/CORIAN) and up to five outputs to choose from - whatever you'd like. In addition, up to two additional towel rails can be attached to the unit. The practical Plug & Play box on the back allows easy installation of a control, whether directly on the unit, by radio or by means of a wired controller. Incl. a chrome-plated towel rail, open on one side, on/off switch, surface temperature: max. 80 °C, vertical wall mount, protection rating: IP X4, surfaces: sheet steel, 6 mm toughened safety glass, 6 mm fine stone or 12 mm corian, plug connection cable: 1 m, quality marking: CE.

## Technical Details

|                                           |                  |                                 |                    |
|-------------------------------------------|------------------|---------------------------------|--------------------|
| <b>Type of IR radiation</b>               | IR-C             | <b>Power consumption</b>        | 500 Watt           |
| <b>Mounting method</b>                    | Surface mounting | <b>Supply voltage</b>           | 230 230 Volt       |
| <b>Mounting direction</b>                 | Vertical         | <b>Frequency supply voltage</b> | 50 50 Hertz        |
| <b>Ceiling mounting</b>                   | No               | <b>Max. surface temperature</b> | 70 Degrees celsius |
| <b>Degree of protection (IP)</b>          | IPX4             | <b>Height</b>                   | 1600 Millimetre    |
| <b>Colour</b>                             | White            | <b>Width</b>                    | 500 Millimetre     |
| <b>With imprint</b>                       | No               | <b>Depth</b>                    | 61 Millimetre      |
| <b>With room temperature controller</b>   | No               | <b>RAL-number</b>               | 0                  |
| <b>With mounting material</b>             | Yes              | <b>Colour temperature</b>       | 0 0 Kelvin         |
| <b>With framework</b>                     | No               |                                 |                    |
| <b>Material framework</b>                 | Other            |                                 |                    |
| <b>Colour framework</b>                   | Other            |                                 |                    |
| <b>Surface treatment</b>                  | Other            |                                 |                    |
| <b>Surface structure front side panel</b> | Smooth           |                                 |                    |
| <b>With lighting cove</b>                 | No               |                                 |                    |
| <b>Dimmable</b>                           | No               |                                 |                    |
| <b>Light outlet</b>                       | Direct           |                                 |                    |