## DATASHEET.



**Product name** LAVABATH2-GL-500-DYL Item number 40919 Manufacturer **ETHERMA** 



## **Product description**

Bathroom infrared heating panel glass customer motif 130x63cm 500W

No

Direct

The LAVA BATH 2.0 DYL infrared heating panel not only provides warm towels due to its built-in towel rack, it can also be customized with a bathroom infrared heating panel. No matter whether a vacation photo or company logo, the customer pattern is applied. And here, you don't even notice that the pattern devices are in fact a contemporary infrared heating panel. It is suitable for vertical wall mounting and ensures maximum safety at all times thanks to the 6 mm thick safety glass and 2 temperature limiters. The innovative technology makes the glass a very good radiation emitter. In combination with the even heat distribution on the surface, the optimally insulated back surface guarantees a high radiation efficiency and thus maximum infrared heat radiation to the front into the room. The frame-less design is modern. There are 3 options to choose from. The practical Plug & Play box at the back of all LAVA 2.0 models allows easy installation of a control, whether directly on the unit, by radio or by means of a wired controller. Incl. a chrome-plated towel rail, open on one side, on/off switch, surface temperature: max. 70 °C, protection rating: IP X4, surfaces: 6 mm ESG safety glass, plug connection cable: 1 m, TÜV, CE marking, 230 V.

## **Technical Details**

Type of IR radiation Mounting method Mounting direction Ceiling mounting	IR-C Surface mounting Vertical No
Degree of protection (IP)	IPX4
Colour With imprint	Multi-coloured Yes
With room temperature	No
controller With mounting material	Yes
With framework	No
Material framework	Other
Colour framework	Other
Surface treatment	Other
Surface structure front side panel	Smooth
With lighting cove	No

Power consumption	500 Watt
Supply voltage	230 230 Volt
Frequency supply voltage	50 50 Hertz
Max. surface temperature	70 Degrees celsius
Height	1300 Millimetre
Width	630 Millimetre
Depth	61 Millimetre
RAL-number	0
Colour temperature	0 0 Kelvin

**Dimmable** 

Light outlet