DATASHEET.



Product name LAVA2-STEEL-500-W Item number 39619 Manufacturer ETHERMA



Product description

infrared heating panel, metal, white, 90x63cm, 500W, 230V

TD C

LAVA 2.0 design infrared heating panels work particularly efficiently and save energy. The 6 mm thick surface material made of safety glass, special ceramic or fine stone, as well as 2 temperature limiters in all panels ensure safety at all times. The innovative technology makes the surfaces a very good radiation emitter. In combination with the even heat distribution on the surface, the optimally insulated back surface guarantees a high radiation efficiency and thus maximum infrared heat radiation to the front into the room. The frame-less design is modern. There are four surfaces (STEEL/GLASS/CERAMIC/STONE) and up to 6 power settings to choose from. The practical Plug & Play box at the back of all LAVA 2.0 models allows easy installation of a control, whether directly on the unit, by radio or by means of a wired controller. With LAVA DYL 2.0 - Design Your LAVA - it is possible to apply your own designs, pictures and photos on the LAVA GLAS 2.0 or LAVA BATH 2.0. On/off switch, surface temperature: max. 95 °C, vertical and horizontal wall mount possible, protection rating: IP X4, surfaces: sheet steel, 6 mm toughened safety glass, 6 mm special ceramic or 6 mm fine stone, plug connection cable: 1 m, certification mark: TÜV, CE marking.

Technical Details

Turns of TD undishion

Type of IR radiation	IR-C
Mounting method	Surface mounting
Mounting direction	Horizontal/vertical
Ceiling mounting	No
Degree of protection (IP)	IPX4
Colour	White
With imprint	No
With room temperature controller	No
With mounting material	Yes
With framework	No
Material framework	Other
Colour framework	White
Surface treatment	Other
Surface structure front side panel	Smooth
With lighting cove	No
Dimmable	No
Light outlet	Direct

Power consumption	500 Watt
Supply voltage	230 230 Volt
Frequency supply voltage	50 50 Hertz
Max. surface temperature	95 Degrees celsius
Height	630 Millimetre
Width	900 Millimetre
Depth	57 Millimetre
RAL-number	9016
Colour temperature	0 0 Kelvin