

# Declaration of Performance (DoP)

 $\epsilon$ 

#### Nr. DoP0011

- 1. Unique identification code for the product type: See appendix 1 (page 2/2)
- Intended use of the construction product:
   Supply of data communication in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke.
- 3. Manufacturer:
  TKF (B.V. Twentsche Kabelfabriek)
  Spinnerstraat 15
  7481 KJ Haaksbergen
  Netherlands

Tel.: +31(0)53 573 22 55 E-mail: info@tkf.eu

www.tkf.eu

- 4. System of assessment and verification of constancy of performance of the construction product asset out in CPR, Annex V: **System 1+**
- 5. Notified body: **NB 0344**
- 6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Cca-s1,d1,a1	EN50575:2014/A1:2016
Dangerous substances	(EC) No 1907/2006 (REACH)	

7. The performance of the product identified is in conformity with the declared performance.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer indentified in this document.

Signed for and on behalf of B.V. Twentsche Kabelfabriek by:

Managing Directo

Haaksbergen, April 26, 2019



## **TKF** CONNECTIVITY SOLUTIONS

 $\epsilon$ 

### Nr. DoP0011

### Appendix 1

Product type	Number of cores	Conductor diameter [mm]	Conductor cross section [mm²]	DoP code
Signaalkabel Cca	2 to 30	0.8		40120C-01
Signaalkabel Cca	2		1.0 to 1.5	40120C-01

Product type	Number of pairs	Conductor diameter [mm]	Conductor cross section [mm²]	DoP code
JHH Cca	1 to 30	0.8		40121C-01
JH(st)H Cca	1 to 24	0.8		40242C-01
JH(st)H Cca	1		1.0 to 2.5	40242C-01
Z1O-JH(st)H Cca	1 to 24	0.8		40329C-01

Product type	Number of quards	Conductor diameter [mm]	Conductor cross section [mm²]	DoP code
JH(st)H Cca	1	0.8		40242C-01