



SIRIUS soft starter S00 12.5 A, 5.5 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC spring-type terminals

### General technical data

|                                                                                            |   |                          |
|--------------------------------------------------------------------------------------------|---|--------------------------|
| product brand name                                                                         |   | SIRIUS                   |
| product feature                                                                            |   |                          |
| • integrated bypass contact system                                                         |   | Yes                      |
| • thyristors                                                                               |   | Yes                      |
| product function                                                                           |   |                          |
| • intrinsic device protection                                                              |   | No                       |
| • motor overload protection                                                                |   | No                       |
| • evaluation of thermistor motor protection                                                |   | No                       |
| • external reset                                                                           |   | No                       |
| • adjustable current limitation                                                            |   | No                       |
| • inside-delta circuit                                                                     |   | No                       |
| product component motor brake output                                                       |   | No                       |
| insulation voltage rated value                                                             | V | 600                      |
| degree of pollution                                                                        |   | 3, acc. to IEC 60947-4-2 |
| reference code according to EN 61346-2                                                     |   | Q                        |
| reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750 |   | G                        |

### Power Electronics

|                                                                                                                |    |              |
|----------------------------------------------------------------------------------------------------------------|----|--------------|
| product designation                                                                                            |    | Soft starter |
| operational current                                                                                            |    |              |
| • at 40 °C rated value                                                                                         | A  | 12.5         |
| • at 50 °C rated value                                                                                         | A  | 12           |
| • at 60 °C rated value                                                                                         | A  | 11           |
| yielded mechanical performance for 3-phase motors                                                              |    |              |
| • at 230 V                                                                                                     |    |              |
| — at standard circuit at 40 °C rated value                                                                     | kW | 3            |
| • at 400 V                                                                                                     |    |              |
| — at standard circuit at 40 °C rated value                                                                     | kW | 5.5          |
| yielded mechanical performance [hp] for 3-phase AC motor at 200/208 V at standard circuit at 50 °C rated value | hp | 3            |
| operating frequency rated value                                                                                | Hz | 50 ... 60    |
| relative negative tolerance of the operating frequency                                                         | %  | -10          |
| relative positive tolerance of the operating frequency                                                         | %  | 10           |
| operating voltage at standard circuit rated value                                                              | V  | 200 ... 480  |
| relative negative tolerance of the operating voltage at standard circuit                                       | %  | -15          |
| relative positive tolerance of the operating voltage at standard circuit                                       | %  | 10           |
| minimum load [%]                                                                                               | %  | 10           |

|                                                                                                                |    |                                                                                                                        |
|----------------------------------------------------------------------------------------------------------------|----|------------------------------------------------------------------------------------------------------------------------|
| continuous operating current [% of I <sub>e</sub> ] at 40 °C                                                   | %  | 115                                                                                                                    |
| power loss [W] at operational current at 40 °C during operation typical                                        | W  | 2                                                                                                                      |
| <b>Control circuit/ Control</b>                                                                                |    |                                                                                                                        |
| type of voltage of the control supply voltage                                                                  |    | AC/DC                                                                                                                  |
| control supply voltage frequency 1 rated value                                                                 | Hz | 50                                                                                                                     |
| control supply voltage frequency 2 rated value                                                                 | Hz | 60                                                                                                                     |
| relative negative tolerance of the control supply voltage frequency                                            | %  | -10                                                                                                                    |
| relative positive tolerance of the control supply voltage frequency                                            | %  | 10                                                                                                                     |
| control supply voltage 1 at AC at 50 Hz                                                                        | V  | 110 ... 230                                                                                                            |
| control supply voltage 1 at AC at 60 Hz                                                                        | V  | 110 ... 230                                                                                                            |
| relative negative tolerance of the control supply voltage at AC at 50 Hz                                       | %  | -20                                                                                                                    |
| relative positive tolerance of the control supply voltage at AC at 50 Hz                                       | %  | 20                                                                                                                     |
| relative negative tolerance of the control supply voltage at AC at 60 Hz                                       | %  | -20                                                                                                                    |
| relative positive tolerance of the control supply voltage at AC at 60 Hz                                       | %  | 20                                                                                                                     |
| control supply voltage 1 at DC                                                                                 | V  | 110 ... 230                                                                                                            |
| relative negative tolerance of the control supply voltage at DC                                                | %  | -20                                                                                                                    |
| relative positive tolerance of the control supply voltage at DC                                                | %  | 20                                                                                                                     |
| display version for fault signal                                                                               |    | red                                                                                                                    |
| <b>Mechanical data</b>                                                                                         |    |                                                                                                                        |
| size of engine control device                                                                                  |    | S00                                                                                                                    |
| width                                                                                                          | mm | 45                                                                                                                     |
| height                                                                                                         | mm | 120                                                                                                                    |
| depth                                                                                                          | mm | 150                                                                                                                    |
| fastening method                                                                                               |    | screw and snap-on mounting                                                                                             |
| mounting position                                                                                              |    | With vertical mounting surface +/-10° rotatable, with vertical mounting surface +/- 10° tiltable to the front and back |
| required spacing with side-by-side mounting                                                                    |    |                                                                                                                        |
| • upwards                                                                                                      | mm | 60                                                                                                                     |
| • at the side                                                                                                  | mm | 15                                                                                                                     |
| • downwards                                                                                                    | mm | 40                                                                                                                     |
| wire length maximum                                                                                            | m  | 300                                                                                                                    |
| number of poles for main current circuit                                                                       |    | 3                                                                                                                      |
| <b>Connections/ Terminals</b>                                                                                  |    |                                                                                                                        |
| type of electrical connection                                                                                  |    |                                                                                                                        |
| • for main current circuit                                                                                     |    | spring-loaded terminals                                                                                                |
| • for auxiliary and control circuit                                                                            |    | spring-loaded terminals                                                                                                |
| number of NC contacts for auxiliary contacts                                                                   |    | 0                                                                                                                      |
| number of NO contacts for auxiliary contacts                                                                   |    | 1                                                                                                                      |
| number of CO contacts for auxiliary contacts                                                                   |    | 0                                                                                                                      |
| type of connectable conductor cross-sections for main contacts for box terminal using the front clamping point |    |                                                                                                                        |
| • solid                                                                                                        |    | 2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> )                                                       |
| • finely stranded with core end processing                                                                     |    | 2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> )                                                       |
| type of connectable conductor cross-sections at AWG cables for main contacts for box terminal                  |    |                                                                                                                        |
| • using the front clamping point                                                                               |    | 2x (16 ... 10)                                                                                                         |
| type of connectable conductor cross-sections for main contacts                                                 |    |                                                                                                                        |
| • solid                                                                                                        |    | 1 ... 4 mm <sup>2</sup>                                                                                                |
| • finely stranded with core end processing                                                                     |    | 1 ... 2.5 mm <sup>2</sup>                                                                                              |
| type of connectable conductor cross-sections for auxiliary contacts                                            |    |                                                                                                                        |

|                                                                                                               |  |                                                                          |
|---------------------------------------------------------------------------------------------------------------|--|--------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• solid</li> <li>• finely stranded with core end processing</li> </ul> |  | 2x (0.25 ... 2.5 mm <sup>2</sup> )<br>2x (0.25 ... 1.5 mm <sup>2</sup> ) |
| <b>type of connectable conductor cross-sections at AWG cables</b>                                             |  |                                                                          |
| <ul style="list-style-type: none"> <li>• for main contacts</li> <li>• for auxiliary contacts</li> </ul>       |  | 16 ... 12<br>2x (24 ... 14)                                              |

#### Ambient conditions

|                                                                                                                                                                                                                               |          |                                                                                                                                                                                                                                                                         |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>installation altitude at height above sea level</b>                                                                                                                                                                        | m        | 5 000                                                                                                                                                                                                                                                                   |
| <b>environmental category</b> <ul style="list-style-type: none"> <li>• during transport according to IEC 60721</li> <li>• during storage according to IEC 60721</li> <li>• during operation according to IEC 60721</li> </ul> |          | 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)<br>1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4<br>3K6 (no formation of ice, no condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 |
| <b>ambient temperature</b> <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> </ul>                                                                                                     | °C<br>°C | -25 ... +60<br>-40 ... +80                                                                                                                                                                                                                                              |
| <b>derating temperature</b>                                                                                                                                                                                                   | °C       | 40                                                                                                                                                                                                                                                                      |
| <b>protection class IP on the front according to IEC 60529</b>                                                                                                                                                                |          | IP20                                                                                                                                                                                                                                                                    |
| <b>touch protection on the front according to IEC 60529</b>                                                                                                                                                                   |          | finger-safe, for vertical contact from the front                                                                                                                                                                                                                        |

#### Certificates/ approvals

|                                 |            |
|---------------------------------|------------|
| <b>General Product Approval</b> | <b>EMC</b> |
|---------------------------------|------------|



[Confirmation](#)



|                                  |                          |              |
|----------------------------------|--------------------------|--------------|
| <b>Declaration of Conformity</b> | <b>Test Certificates</b> | <b>other</b> |
|----------------------------------|--------------------------|--------------|



[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

[Confirmation](#)

#### UL/CSA ratings

|                                                                                                                                                                                                                                                                                                                                                      |          |             |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------------|
| <b>yielded mechanical performance [hp] for 3-phase AC motor</b> <ul style="list-style-type: none"> <li>• at 220/230 V <ul style="list-style-type: none"> <li>— at standard circuit at 50 °C rated value</li> </ul> </li> <li>• at 460/480 V <ul style="list-style-type: none"> <li>— at standard circuit at 50 °C rated value</li> </ul> </li> </ul> | hp<br>hp | 3<br>7.5    |
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                          |          | B300 / R300 |

#### Further information

**Simulation Tool for Soft Starters (STS)**

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW3017-2BB14>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW3017-2BB14>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW3017-2BB14>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW3017-2BB14&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW3017-2BB14&lang=en)

