



AS-i compact module K60 digital 4 DI/4 DQ, IP67 4 x input, maximum 200 mA 4 x output, 1 A, 24 V DC 8 x M12 standard sockets Mounting plate 3RK1901-0CA00 must be ordered separately

General technical data	
design of the product	digital I/O modules for operation in the field, IP67 - K60
Type	4 inputs / 4 outputs
design of the slave type	standard slave
I/O configuration	7
ID/ID2 code	0/F
Number I/O sockets	8
type of electrical connection of the inputs and outputs	M12 screw-type terminals
AS interface total current input max	270 mA
operating voltage according to AS-Interface specification	26.5 ... 31.6 V
Ground terminal	PIN5 of each M12 socket is connected to the grounding wrist strap in the mounting plate using a pin
Addressing	front addressing socket
Delivery note	the modules are delivered without mounting plate
Note 2	An external additional supply (AUX POWER) of 20 to 30 V DC is required for the supply of the output circuits. The additional supply must comply with VDE 0106 (PELV), protection class III.
Sensor supply	
type of voltage supply for power supply	using AS-Interface
input voltage	20 ... 30 V
property of the sensor supply short-circuit and overload resistant	Yes
ampacity of the sensor supply for all inputs	
• at ambient temperature 40 °C	200 mA
Inputs	
number of digital inputs	4
type of connection technology	2- and 3-wire technology
Input circuit	PNP transistor
type of voltage of the input voltages	DC
Inputs switching level High min	10 V
input current at digital input	
• for signal <1> minimum	6 mA
• with signal <0> maximum	1.5 mA
Inputs	
• sensor supply using AS-Interface	short-circuit and overload resistant
• socket assignment	
— PIN 1	sensor supply L+
— PIN 2	data input I
— PIN 3	sensor supply L-
— PIN 4	data input I
— PIN 5	ground terminal

design of the pin assignment of the inputs		standard assignment	
Outputs			
number of digital outputs		4	
type of voltage of output voltages		DC	
Outputs external power supply 24 V DC		using black AS-Interface flat cable	
ampacity of the semiconductor output at DC-13 at 24 V		1 A	
Outputs aggregate current max		4 A	
type of switching output		PNP transistor	
design of the pin assignment of the outputs		standard assignment	
Outputs socket assignment		3 = "-", 4 = output, 5 = ground terminal	
property of the output short-circuit proof		Yes	
Outputs			
• short-circuit protection • induction protection • watchdog		built-in built-in built-in	
Assignment of the data bits			
Assignment of data bits			
• socket • socket 2 • socket 3 • socket 4 • socket 5 • socket 6 • socket 7 • socket 8		PIN 2/4 = IN1 (D0) PIN 2/4 = IN2 (D1) PIN2/ 4 = IN3 (D2) PIN 2/4 = IN4 (D3) PIN4 = OUT1 (D0) PIN4 = OUT2 (D1) PIN4 = OUT3 (D2) PIN4 = OUT4 (D3)	
Ambient conditions			
ambient temperature			
• during operation • during storage		-25 ... +85 °C -40 ... +85 °C	
protection class IP		IP67	
Display			
Status display			
• display of I/Os • display of Uaux • display of AS-Interface/diagnostics		yellow LED green LED green/red LED	
Mechanical data			
width		60 mm	
height		152 mm	
depth		29 mm	
fastening method		standard rail mounting/wall mounting using mounting plate for K60 compact module	
shock resistance		15g / 11 ms	
Certificates/ approvals			
General Product Approval		EMC	Declaration of Conformity
 CSA Confirmation  UL   RCM  EG-Konf.			
Test Certificates			
Marine / Shipping			
Special Test Certificate  ABS  BUREAU VERITAS  LRS  PRS  RINA			
Marine / Shipping		other	



[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1400-1DQ03-0AA3>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1400-1DQ03-0AA3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1400-1DQ03-0AA3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1400-1DQ03-0AA3&lang=en



last modified:

3/10/2021