

PRODUCT DATASHEET

NAV-E 68 W E27

VIALOX® NAV®-E Plug-in | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Streets
- Outdoor lighting
- Industrial installations
- Luminaires that use mercury vapor lamps HQL® 80 W, 125 W, 250 W, 400 W
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- No modifications to existing luminaire components required




TECHNICAL DATA

Electrical data

Nominal wattage	68 W
Construction wattage	70.00 W
Nominal voltage	102 V
Ignition voltage	0.198 kVp
Nominal current	0.85 A
PFC capacitor at 50 Hz	8 µF

Photometrical data

Luminous flux	5400 lm
Luminous efficacy	77 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.92
Rated LLMF at 4,000 h	0.88
Rated LLMF at 6,000 h	0.85
Rated LLMF at 8,000 h	0.84
Rated LLMF at 12,000 h	0.83
Rated LLMF at 16,000 h	0.80
Rated LLMF at 20,000 h	0.75
UV protection	No



Dimensions & Weight

Overall length	155.00 mm
Diameter	71 mm

Product weight	50.00 g
----------------	---------

Temperatures & operating conditions

Maximum permitted outer bulb temperature	400 °C
Maximum permitted base edge temperature	210 °C

Lifespan

Lifespan	20000 h
Rated lamp survival factor at 2,000 h	0.98
Rated lamp survival factor at 4,000	0.98
Rated lamp survival factor at 6,000	0.97
Rated lamp survival factor at 8,000 h	0.96
Rated lamp survival factor at 12,000 h	0.90
Rated lamp survival factor at 16,000	0.80
Rated lamp survival factor at 20,000 h	0.50
Lifespan B10	12000 h
Lifespan B5	9000 h
Lifespan B50	20000 h

Additional product data

Base (standard designation)	E27
Mercury content	14.7 mg
Design / version	Coated

Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	No

Certificates & Standards

Energy efficiency class	G
Energy consumption	70.00 kWh/1000h

Country-specific categorizations

ILCOS	SEQ-68-H/I/S-E27-71/152
Order reference	NAV-E 68W E27

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	HPS
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	155.00 mm
Height	71 mm
Width	71 mm
Chromaticity coordinate x	0,535
Chromaticity coordinate y	0,420
Beam angle correspondence	SPHERE_360
EPREL ID	546568
Model number	AC34360

Safety advice

- Control gear must be suitable for the higher operating current of the NAV® Plug-in lamps. The maximum permissible winding temperature as defined in VDE and IEC specifications must not be exceeded. In case of doubt, consult the manufacturer of the luminaire or control gear.

ADDITIONAL PRODUCT INFORMATION

- Control gear must be suitable for the higher operating current of the NAV® Plug-in lamps. The maximum permissible winding temperature as defined in VDE and IEC specifications must not be exceeded. In case of doubt, consult the manufacturer of the luminaire or control gear.

DOWNLOAD DATA

Documents and certificates	
	User instruction
	Declarations Of Conformity CE

Documents and certificates	
	Certificates
Photometric and lighting design files	
	Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321345462	Round wrap 1	75 mm x 75 mm x 165 mm	83.00 g	0.93 dm ³
4008321345479	Shipping box 24	360 mm x 285 mm x 355 mm	2039.00 g	36.42 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.