

Sample image

## Datasheet

**Article number:** 70009118

**Designation:** CH10.A007.FT2.F785

**Description:** Switch

|                                                                                                                                                                 |                          |                          |                                                                  |                 |                           |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------|------------------------------------------------------------------|-----------------|---------------------------|--|
| IEC 60947-3 EN 60947-3, VDE 0660 Teil 107                                                                                                                       |                          |                          |                                                                  |                 |                           |  |
| Rated insulation voltage Ui                                                                                                                                     |                          |                          |                                                                  |                 |                           |  |
| Voltage (V) AC / DC                                                                                                                                             |                          |                          |                                                                  |                 |                           |  |
| 690 AC / DC                                                                                                                                                     |                          |                          |                                                                  |                 |                           |  |
| Rated uninterrupted current Iu/Ith                                                                                                                              |                          |                          |                                                                  |                 |                           |  |
| Current (A)                                                                                                                                                     | Ambient temperature (°C) | Peak temperature (°C)    | additional requirements                                          |                 |                           |  |
| 20                                                                                                                                                              | 55                       | 60                       | Ambient temperature +55°C during 24 hours with peaks up to +60°C |                 |                           |  |
| Rated operational current Ie                                                                                                                                    |                          |                          |                                                                  |                 |                           |  |
| Utilization category                                                                                                                                            |                          |                          | Voltage (V)                                                      |                 | Current (A)               |  |
| AC-15                                                                                                                                                           |                          |                          | 220 - 240                                                        |                 | 6                         |  |
| AC-15                                                                                                                                                           |                          |                          | 380 - 440                                                        |                 | 4                         |  |
| Rated operational power                                                                                                                                         |                          |                          |                                                                  |                 |                           |  |
| Utilization category                                                                                                                                            |                          | Voltage (V)              | No. of phases                                                    | No. of poles    | Power (kW)                |  |
| AC-3                                                                                                                                                            |                          | 220 - 240                | 3                                                                | 3               | 3                         |  |
| AC-3                                                                                                                                                            |                          | 380 - 440                | 3                                                                | 3               | 5,50                      |  |
| AC-3                                                                                                                                                            |                          | 660 - 690                | 3                                                                | 3               | 5,50                      |  |
| AC-3                                                                                                                                                            |                          | 220 - 240                | 1                                                                | 2               | 2,20                      |  |
| AC-3                                                                                                                                                            |                          | 380 - 440                | 1                                                                | 2               | 3                         |  |
| AC-23A                                                                                                                                                          |                          | 220 - 240                | 3                                                                | 3               | 3,70                      |  |
| AC-23A                                                                                                                                                          |                          | 380 - 440                | 3                                                                | 3               | 7,50                      |  |
| AC-23A                                                                                                                                                          |                          | 660 - 690                | 3                                                                | 3               | 7,50                      |  |
| AC-23A                                                                                                                                                          |                          | 220 - 240                | 1                                                                | 2               | 2,50                      |  |
| AC-23A                                                                                                                                                          |                          | 380 - 440                | 1                                                                | 2               | 3,70                      |  |
| Max. Fuse rating IEC                                                                                                                                            |                          |                          |                                                                  |                 |                           |  |
| Fuse characteristic                                                                                                                                             |                          |                          | No. of Fuses                                                     |                 | Current (A)               |  |
| gG                                                                                                                                                              |                          |                          | 1                                                                |                 | 25                        |  |
| UL60947-4-1 , UL508                                                                                                                                             |                          |                          |                                                                  |                 |                           |  |
| Nominal Voltage                                                                                                                                                 |                          |                          |                                                                  |                 |                           |  |
| Voltage (V) AC / DC                                                                                                                                             |                          |                          |                                                                  |                 |                           |  |
| 600 AC                                                                                                                                                          |                          |                          |                                                                  |                 |                           |  |
| Rated insulation voltage Ui                                                                                                                                     |                          |                          |                                                                  |                 |                           |  |
| Voltage (V) AC / DC                                                                                                                                             |                          |                          |                                                                  |                 |                           |  |
| 600 AC                                                                                                                                                          |                          |                          |                                                                  |                 |                           |  |
| Rated thermal current                                                                                                                                           |                          |                          |                                                                  |                 |                           |  |
| Current (A)                                                                                                                                                     |                          | Ambient temperature (°C) |                                                                  | Additional Text |                           |  |
| 20                                                                                                                                                              |                          | 0 - 40                   |                                                                  | --              |                           |  |
| Horsepower rating                                                                                                                                               |                          |                          |                                                                  |                 |                           |  |
| Across-the-Line Motor Starting                                                                                                                                  | Voltage (V)              | No. of phases            | No. of poles                                                     | Power (HP)      | Ambient temperature [°C]  |  |
| DOL                                                                                                                                                             | 110 - 120                | 1                        | 2                                                                | 0,50            | 40                        |  |
| DOL                                                                                                                                                             | 220 - 240                | 1                        | 2                                                                | 1               | 40                        |  |
| DOL                                                                                                                                                             | 277 - 277                | 1                        | 2                                                                | 2               | 40                        |  |
| DOL                                                                                                                                                             | 440 - 480                | 1                        | 2                                                                | 2               | 40                        |  |
| DOL                                                                                                                                                             | 550 - 600                | 1                        | 2                                                                | 2               | 40                        |  |
| DOL                                                                                                                                                             | 110 - 120                | 3                        | 3                                                                | 1,50            | 40                        |  |
| DOL                                                                                                                                                             | 220 - 240                | 3                        | 3                                                                | 3               | 40                        |  |
| DOL                                                                                                                                                             | 440 - 480                | 3                        | 3                                                                | 5               | 40                        |  |
| DOL                                                                                                                                                             | 550 - 600                | 3                        | 3                                                                | 5               | 40                        |  |
| Pilot duty rating code                                                                                                                                          |                          |                          |                                                                  |                 |                           |  |
| Duty Code                                                                                                                                                       |                          |                          |                                                                  |                 |                           |  |
| A600                                                                                                                                                            |                          |                          |                                                                  |                 |                           |  |
| SCCR / Max. fuse rating                                                                                                                                         |                          |                          |                                                                  |                 |                           |  |
| Conditions of acceptability                                                                                                                                     |                          |                          |                                                                  |                 |                           |  |
| These devices are suitable for use on circuits capable of delivering not more than 5kA rms symmetrical amperes, 600V ac max. when protected by Class RK1 fuses. |                          |                          |                                                                  |                 |                           |  |
| Temp. rating of wire                                                                                                                                            |                          |                          |                                                                  |                 |                           |  |
| Temperature rating (°C)                                                                                                                                         |                          | Current (A) Text         |                                                                  |                 |                           |  |
| 60 - 75                                                                                                                                                         |                          | -- Use copper wire only  |                                                                  |                 |                           |  |
| General Use                                                                                                                                                     |                          |                          |                                                                  |                 |                           |  |
| AC / DC                                                                                                                                                         | Voltage (V)              | Current (A)              | No. of phases                                                    | No. of poles    | No. of contacts in series |  |
| AC                                                                                                                                                              | 277                      | 20                       | 1                                                                | 1               | 1                         |  |
| AC                                                                                                                                                              | 600                      | 20                       | 1                                                                | 2               | 1                         |  |

| General Use                                       |                   |                               |                          |                                                                                     |                           |                      |            |                          |
|---------------------------------------------------|-------------------|-------------------------------|--------------------------|-------------------------------------------------------------------------------------|---------------------------|----------------------|------------|--------------------------|
| AC / DC                                           | Voltage (V)       | Current (A)                   | No. of phases            | No. of poles                                                                        | No. of contacts in series |                      |            |                          |
| AC                                                | 600               | 20                            | 3                        | 3                                                                                   | 1                         |                      |            |                          |
| CSA                                               |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| Nominal Voltage                                   |                   |                               |                          |                                                                                     |                           |                      |            |                          |
|                                                   |                   |                               |                          | Voltage (V) AC / DC                                                                 |                           |                      |            |                          |
|                                                   |                   |                               |                          | 600 AC                                                                              |                           |                      |            |                          |
| Rated insulation voltage Ui                       |                   |                               |                          |                                                                                     |                           |                      |            |                          |
|                                                   |                   |                               |                          | Voltage (V) AC / DC                                                                 |                           |                      |            |                          |
|                                                   |                   |                               |                          | 600 AC                                                                              |                           |                      |            |                          |
| Rated thermal current                             |                   |                               |                          |                                                                                     |                           |                      |            |                          |
|                                                   |                   | Current (A)                   | Ambient temperature (°C) |                                                                                     | Additional Text           |                      |            |                          |
|                                                   |                   | 20                            | 0 - 40                   |                                                                                     | --                        |                      |            |                          |
| Horsepower rating                                 |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| Across-the-Line Motor Starting                    |                   |                               |                          | Voltage (V)                                                                         | No. of phases             | No. of poles         | Power (HP) | Ambient temperature [°C] |
| DOL                                               |                   |                               |                          | 110 - 120                                                                           | 1                         | 2                    | 0,50       | 40                       |
| DOL                                               |                   |                               |                          | 220 - 240                                                                           | 1                         | 2                    | 1          | 40                       |
| DOL                                               |                   |                               |                          | 277 - 277                                                                           | 1                         | 2                    | 2          | 40                       |
| DOL                                               |                   |                               |                          | 440 - 480                                                                           | 1                         | 2                    | 2          | 40                       |
| DOL                                               |                   |                               |                          | 550 - 600                                                                           | 1                         | 2                    | 2          | 40                       |
| DOL                                               |                   |                               |                          | 110 - 120                                                                           | 3                         | 3                    | 1,50       | 40                       |
| DOL                                               |                   |                               |                          | 220 - 240                                                                           | 3                         | 3                    | 3          | 40                       |
| DOL                                               |                   |                               |                          | 440 - 480                                                                           | 3                         | 3                    | 5          | 40                       |
| DOL                                               |                   |                               |                          | 550 - 600                                                                           | 3                         | 3                    | 5          | 40                       |
| Pilot duty rating code                            |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| Duty Code                                         |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| A600                                              |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| Temp. rating of wire                              |                   |                               |                          |                                                                                     |                           |                      |            |                          |
|                                                   |                   |                               | Temperature rating (°C)  |                                                                                     | Current (A) Text          |                      |            |                          |
|                                                   |                   |                               | 75                       |                                                                                     | -- --                     |                      |            |                          |
| General Use                                       |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| AC / DC                                           | Voltage (V)       | Current (A)                   | No. of phases            | No. of poles                                                                        | No. of contacts in series |                      |            |                          |
| AC                                                | 277               | 20                            | 1                        | 1                                                                                   | 1                         |                      |            |                          |
| AC                                                | 600               | 20                            | 1                        | 2                                                                                   | 1                         |                      |            |                          |
| AC                                                | 600               | 20                            | 3                        | 3                                                                                   | 1                         |                      |            |                          |
| GENERAL TECHNICAL INFORMATION                     |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| Size of conductor                                 |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| composition of conductor                          | Min. / Max. value | No. of conductor per terminal |                          | Cross section (mm²) or (AWG/kcmil)                                                  |                           | Material of the wire |            |                          |
| solid wire                                        | Min.              | 1                             |                          | 0.75mm²                                                                             |                           | Copper               |            |                          |
| solid wire                                        | Min.              | 2                             |                          | 0.75mm²                                                                             |                           | Copper               |            |                          |
| flexible wire                                     | Min.              | 1                             |                          | 0.75mm²                                                                             |                           | Copper               |            |                          |
| flexible wire                                     | Min.              | 2                             |                          | 0.75mm²                                                                             |                           | Copper               |            |                          |
| flexible wire                                     | Max.              | 2                             |                          | AWG 12                                                                              |                           | Copper               |            |                          |
| flexible wire                                     | Max.              | 2                             |                          | 2.5mm²                                                                              |                           | Copper               |            |                          |
| Single-core or stranded wire                      | Max.              | 2                             |                          | AWG 10                                                                              |                           | Copper               |            |                          |
| Single-core or stranded wire                      | Max.              | 2                             |                          | 4mm²                                                                                |                           | Copper               |            |                          |
| flexible wire with ferrule according to DIN 46228 | Min.              | 1                             |                          | 0.75mm²                                                                             |                           | Copper               |            |                          |
| flexible wire with ferrule according to DIN 46228 | Min.              | 2                             |                          | 0.75mm²                                                                             |                           | Copper               |            |                          |
| flexible wire with ferrule according to DIN 46228 | Max.              | 2                             |                          | 2.5mm²                                                                              |                           | Copper               |            |                          |
| Stripping length                                  |                   |                               |                          |                                                                                     |                           |                      |            |                          |
|                                                   |                   |                               |                          | Length (mm) --                                                                      |                           |                      |            |                          |
|                                                   |                   |                               |                          |  |                           |                      |            |                          |
|                                                   |                   |                               |                          | 9                                                                                   |                           |                      |            |                          |
| Recommended screw driver                          |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| Type of screw driver                              |                   |                               |                          | Value                                                                               |                           |                      |            |                          |
| Cross Screwdriver                                 |                   |                               |                          | PH1                                                                                 |                           |                      |            |                          |
| Slot screwdriver according to DIN 5264            |                   |                               |                          | 0,8x4                                                                               |                           |                      |            |                          |
| Tightening torque of screws                       |                   |                               |                          |                                                                                     |                           |                      |            |                          |
|                                                   |                   |                               | tightening torque (Nm)   |                                                                                     | tightening torque (lb-in) |                      |            |                          |
|                                                   |                   |                               | 1                        |                                                                                     | 9                         |                      |            |                          |
| Approbations                                      |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| Specification                                     |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| EAC                                               |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| CE marking                                        |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| UK Directives                                     |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| CSA C.22.2 No.14                                  |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| GB/T14048.3                                       |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| General Information                               |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| Text                                              |                   |                               |                          |                                                                                     |                           |                      |            |                          |
| - Do not lubricate or treat contacts.             |                   |                               |                          |                                                                                     |                           |                      |            |                          |

## General Information

### Text

- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.
- Use copper wire only. Do not coat the wire end with tin.
- Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.
- After installation of the switches the spacings between the terminals must be sufficient to fulfill the requirement of the applicable standards.

## Waste Electrical & Electronic Equipment (WEEE)

| Picture name                                                                     | Description                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Do not throw in the trash as care must be taken to ensure environmentally sound disposal and recycling. Please either use an environmentally friendly waste disposal company; return to the supplier for disposal; or return direct to the manufacturer, Kraus & Naimer. You can find local Kraus & Naimer offices at <a href="http://www.krausnaimer.com">www.krausnaimer.com</a> |

## Proposition 65


| Picture name                                                                     | Description                                                                                                                                                                                                                             |
|----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | WARNING: This product can expose you to chemicals including nickel and lead, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> . |

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal


## Mounting-FT2



|                      |   |                   |
|----------------------|---|-------------------|
| IP - Code front side |   | IP66, IP67, IP69k |
| Stages               |   | 1,00 - 12,00      |
| A                    | H | 3,20 mm           |
| A+_tol.              | H | 0,20 mm           |
| A-_tol.              | H | 0,00 mm           |
| B                    | H | 24,10 mm          |
| B+_tol.              | H | 0,40 mm           |
| B-_tol.              | H | 0,00 mm           |
| C                    | Ø | 22,30 mm          |
| C+_tol.              | Ø | 0,40 mm           |
| C-_tol.              | Ø | 0,00 mm           |
| D                    | H | <= 6,00 mm        |
| E                    | □ | 48,00 mm          |
| M                    | ↺ | 0,50 Nm           |
| M1                   | ↺ | 1,80 Nm           |



## Wiring diagram

CH10.A007.FT2



## Switch program


CH10.A007.FT2

|  Kraus & Naimer |     | CH10                                                                              |   | A007 |   | E  |    | Page 1 of 1 |    |    |    |    |    |
|--------------------------------------------------------------------------------------------------|-----|-----------------------------------------------------------------------------------|---|------|---|----|----|-------------|----|----|----|----|----|
| Face Plate                                                                                       |     |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                 |     | 1                                                                                 | 3 | 5    | 7 | 9  | 11 | 13          | 15 | 17 | 19 | 21 | 23 |
|                                                                                                  |     |  |   |      |   |    |    |             |    |    |    |    |    |
| Switching Angle <input type="text" value="45"/>                                                  |     | 2                                                                                 | 4 | 6    | 8 | 10 | 12 | 14          | 16 | 18 | 20 | 22 | 24 |
| Total switching Angle <input type="text" value="270"/>                                           |     |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| TR                                                                                               | 225 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 240 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| ST                                                                                               | 255 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 270 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| RS                                                                                               | 285 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 300 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| R0                                                                                               | 315 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 330 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| S0                                                                                               | 345 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 0   |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| T0                                                                                               | 15  |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 30  |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| TR                                                                                               | 45  |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 60  |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| ST                                                                                               | 75  |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 90  |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| RS                                                                                               | 105 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 120 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| R0                                                                                               | 135 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 150 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| S0                                                                                               | 165 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 180 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
| T0                                                                                               | 195 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |
|                                                                                                  | 210 |                                                                                   |   |      |   |    |    |             |    |    |    |    |    |

Version: 44

## Face plate

S0.F785/A10.E1L



## HANDLES

**Designation:** S0C.G251

**Handle colour:** "1" black

