



Sample image

## LATERAL AUXILIARY CONTACTS

for KG20 - KG317 and KH(R)16 - KH(R)25B

**Designation:** K2.H010/A11-E

**Kind of contact operation:** "A" not overlapping

**Contact combination:** "11" 1 NO + 1 NC

**Type of mounting:** "-E" for type of mounting E

### IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

#### Rated insulation voltage Ui

Voltage (V) AC / DC  
690 AC

### UL60947-4-1, UL508

#### Nominal Voltage

Voltage (V) AC / DC  
600 AC

#### Rated insulation voltage Ui

Voltage (V) AC / DC  
600 AC

#### Rated thermal current

Current (A) Ambient temperature (°C) Additional Text  
10 0 - 40 -

#### Pilot duty rating code

Duty Code

A600

#### General Use

| AC / DC | Voltage (V) | Current (A) | No. of phases | No. of poles | No. of contacts in series |
|---------|-------------|-------------|---------------|--------------|---------------------------|
| AC      | 600         | 10          | 1             | 1            | 1                         |

#### General Information

Text

- Use copper wire only. Do not coat the wire end with tin.

#### CSA

#### Temp. rating of wire

Temperature rating (°C) Current (A) Text  
75 - only

### GENERAL TECHNICAL INFORMATION

#### Size of conductor

| composition of conductor                          | Min. / Max. value | No. of conductor per terminal | Cross section (mm <sup>2</sup> ) or (AWG/kcmil) | Material of the wire |
|---------------------------------------------------|-------------------|-------------------------------|-------------------------------------------------|----------------------|
| flexible wire                                     | Max.              | 2                             | 2.5mm <sup>2</sup>                              | Copper               |
| flexible wire                                     | Max.              | 2                             | AWG 14                                          | Copper               |
| Single-core or stranded wire                      | Max.              | 2                             | AWG 12                                          | Copper               |
| Single-core or stranded wire                      | Max.              | 2                             | 2.5mm <sup>2</sup>                              | Copper               |
| flexible wire with ferrule according to DIN 46228 | Max.              | 2                             | 2.5mm <sup>2</sup>                              | Copper               |

#### Stripping length

Length (mm) -

8

#### Recommended screw driver

Type of screw driver

Cross Screwdriver

Slot screwdriver according to DIN 5264

Value

PH1

0,8x4

### KG20 - KG100C

