



Sample image

Datasheet

Article number: 70006974

Designation: CA25B.A201.EF

Description: Switch

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107					
Tension assignée d'isolement Ui					
Tension (V) AC / DC					
690 AC / DC					
Courant Ininterrompu et thermique conventionnel Iu/Ith					
Intensité (A)	Température Ambiante (°)	Température Maxi (*)	Spécification complémentaire		
32	55	60	Température ambiante +55°C durant 24 heures avec point à +60°C		
Courant assigné d'emploi Ie					
Catégorie d'emploi			Tension (V)		Intensité (A)
AC-15			220 - 240		12
AC-15			380 - 440		6
Puissance assignée d'emploi					
Catégorie d'emploi		Tension (V)	Nb de phases	Nb de pôles	Puissance (kW)
AC-3		220 - 240	3	3	5,50
AC-3		380 - 440	3	3	11
AC-3		660 - 690	3	3	11
AC-3		220 - 240	1	2	4
AC-3		380 - 440	1	2	5,50
AC-23A		220 - 240	3	3	7,50
AC-23A		380 - 440	3	3	15
AC-23A		660 - 690	3	3	15
AC-23A		220 - 240	1	2	4
AC-23A		380 - 440	1	2	7,50
Protection par fusible (IEC)					
Caractéri			Nombre de fusible		Intensité (A)
gG			1		35
UL60947-4-1 , UL508					
Nominal Voltage					
Tension (V) AC / DC					
300 AC					
Tension assignée d'isolement Ui					
Tension (V) AC / DC					
300 AC					
Rated thermal current					
Intensité (A)		Température Ambiante (°)		Additional Text	
30		0 - 40		--	
Horsepower rating					
Across-the-Line Motor Starting	Tension (V)	Nb de phases	Nb de pôles	Power (HP)	Ambient temperature [°C]
Reversing	110 - 120	1	2	1,50	40
Reversing	220 - 240	1	2	3	40
Reversing	277 - 277	1	2	3	40
Reversing	110 - 120	3	3	2	40
Reversing	220 - 240	3	3	3	40
DOL	110 - 120	1	2	2	40
DOL	220 - 240	1	2	5	40
DOL	277 - 277	1	2	5	40
DOL	110 - 120	3	3	5	40
DOL	220 - 240	3	3	10	40
Pilot duty rating code					
Duty Code					
A300					
SCCR / Max. fuse rating					
Conditions of acceptability					
These devices are suitable for use on circuits capable of delivering not more than 5000 rms symmetrical amperes, 600V ac max. when protected by Class RK1 fuses.					
Temp. rating of wire					
Temperature rating (°C)		Intensité (A)		Text	
60 - 75		--		Use copper wire only	
General Use					
AC / DC	Tension (V)	Intensité (A)	Nb de phases	Nb de pôles	No. of contacts in series
AC	120	30	1	2	1


General Use								
AC / DC	Tension (V)	Intensité (A)	Nb de phases	Nb de pôles	No. of contacts in series			
AC	240	30	3	3	1			
AC	277	30	1	2	1			
CSA								
Nominal Voltage								
			Tension (V) AC / DC					
			300 AC					
Tension assignée d'isolement Ui								
			Tension (V) AC / DC					
			300 AC					
Rated thermal current								
		Intensité (A)	Température Ambiante (°)		Additional Text			
		30	0 - 40		--			
Horsepower rating								
Across-the-Line Motor Starting				Tension (V)	Nb de phases	Nb de pôles	Power (HP)	Ambient temperature [°C]
DOL				110 - 120	1	2	2	40
DOL				220 - 240	1	2	5	40
DOL				277 - 277	1	2	5	40
DOL				110 - 120	3	3	5	40
DOL				220 - 240	3	3	10	40
Pilot duty rating code								
Duty Code								
A300								
Temp. rating of wire								
			Temperature rating (°C)	Intensité (A)		Text		
			75			-- only		
General Use								
AC / DC	Tension (V)	Intensité (A)	Nb de phases	Nb de pôles	No. of contacts in series			
AC	300	30	1	1	1			
GENERAL TECHNICAL INFORMATION								
Tightening torque of screws								
			tightening torque (Nm)		tightening torque (lb-in)			
			1,30		12			
Stripping length								
			Length (mm) --					
			11 STRIPPINGLENGTH					
Size of conductor								
composition of conductor		Min. / Max. value	No. of conductor per terminal		Cross section (mm²) or (AWG/kcmil)		Material of the wire	
flexible wire		Max.			2 AWG 10		Copper	
flexible wire		Max.			2 4mm²		Copper	
Single-core or stranded wire		Max.			2 6mm²		Copper	
Single-core or stranded wire		Max.			2 AWG 8		Copper	
flexible wire with ferrule according to DIN 46228		Max.			2 4mm²		Copper	
Approbations								
Specification								
EAC								
CE marking								
UK Directives								
CSA C.22.2 No.14								
GB/T14048.3								
Recommandations concernant le tournevis								
Type			Value					
Tournevis cruciforme			PH2					
Slot screwdriver according to DIN 5264			1x5,5					
General Information								
Text								
- Ne jamais lubrifier ou traiter les contacts.								
- Les commutateurs ne peuvent être montés, branchés et mis en service que par une personne qualifiée selon les règles techniques en vigueur.								
- Use copper wire only. Do not coat the wire end with tin.								
- Les bornes qui ne sont pas supposées être utilisées pour le raccordement de l'appareil sont livrées serrées et ne doivent pas être desserrées. Si toutefois ces bornes sont malgré tout ouvertes accidentellement, vérifier qu'aucun shunt n'est manquant. Le câblage terminé, s'assurer que toutes les bornes sont serrées.								
- Après mise en place des les commutateurs l'espace entre bornes doit être suffisant pour répondre aux exigences des normes en vigueur.								
Waste Electrical & Electronic Equipment (WEEE)								
Picture name		Description						
		Do not throw in the trash as care must be taken to ensure environmentally sound disposal and recycling. Please either use an environmentally friendly waste disposal company; return to the supplier for disposal; or return direct to the manufacturer, Kraus & Naimer. You can find local Kraus & Naimer offices at www.krausnaimer.com						
Proposition 65								
Picture name		Description						
		WARNING: This product can expose you to chemicals including nickel and lead, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov .						

Type de contacts: Rigid contact bridge

Revêtement des Contacts: Silver

Types de raccordement: Screw terminal

Fixation-EF



IP - Code front side		IP66, IP67, IP69k
Stages		1,00 - 12,00
A	□	48,00 mm
B	∅	5,00 mm
C	∅	19,00 - 22,00 mm
D	H	<= 4,00 mm
E	H	64,00 mm
F	H	78,00 mm
G	H	7,40 mm
M	M̂	0,70 Nm
M1	M̂	0,90 Nm



Wiring diagram

CA25B.A201.EF





Switch program

CA25B.A201.EF



Kraus & Naimer


CA25B
A201
Page 1 of 1

Face Plate													
		1357911131517192123											
													
Switching Angle 60 Total switching Angle 60		2	4	6	8	10	12	14	16	18	20	22	24
0	0												
	15												
	30												
	45												
1	60												
	75												
	90												
	105												
	120												
	135												
	150												
	165												
	180												
	195												
	210												
	225												
	240												
	255												
	270												
	285												
	300												
	315												
	330												
	345												

Version: 118

Face plate

S1.F070/A1B.PEL



HANDLES

Designation: S1B.G251

Handle colour: "1" black

