

Sample image

Datasheet

Article number: 70018395

Designation: KG64B.T903.E

Description: Switch Local Disconnecter

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107					
Tension assignée d'isolement Ui					
Tension (V) AC / DC					
690 AC					
Courant Ininterrompu et thermique conventionnel Iu/Ith					
Intensité (A)	Température Ambiante (°)	Température Maxi (°)	Spécification complémentaire		
63	50	55	Température ambiante +50°C durant 24 heures avec point à +55°C		
Courant assigné d'emploi Ie					
Catégorie d'emploi		Tension (V)		Intensité (A)	
AC-32A		20 - 400		63	
Puissance assignée d'emploi					
Catégorie d'emploi	Tension (V)	Nb de phases	Nb de pôles	Puissance (kW)	
AC-3	220 - 240	3	3	11	
AC-3	380 - 440	3	3	18,50	
AC-3	660 - 690	3	3	15	
AC-23A	220 - 240	3	3	11	
AC-23A	380 - 440	3	3	22	
AC-23A	660 - 690	3	3	18,50	
Protection par fusible (IEC)					
Caractéri		Nombre de fusible		Intensité (A)	
gG		1		63	
UL60947-4-1 , UL508					
Nominal Voltage					
Tension (V) AC / DC					
600 AC					
Tension assignée d'isolement Ui					
Tension (V) AC / DC					
600 AC					
Rated thermal current					
Intensité (A)		Température Ambiante (°)		Additional Text	
60		0 - 40		--	
Horsepower rating					
Across-the-Line Motor Starting		Tension (V)	Nb de phases	Nb de pôles	Power (HP)
DOL		110 - 120	1	2	3
DOL		220 - 240	1	2	7,50
DOL		277 - 277	1	2	7,50
DOL		415 - 415	1	2	10
DOL		440 - 480	1	2	15
DOL		550 - 600	1	2	15
DOL		110 - 120	3	3	5
DOL		220 - 240	3	3	15
DOL		415 - 415	3	3	20
DOL		440 - 480	3	3	30
DOL		550 - 600	3	3	40
SCCR / Max. fuse rating					
Conditions of acceptability					
This device is suitable for use on circuits capable of delivering not more than 10kA rms symmetrical amperes, 600V ac max. when protected by Type RK1 fuses.					
Suitable for use on a circuit capable of delivering not more than 65000 rms symmetrical amperes 600V max., when protected by 70A Class J fuses.					
Temp. rating of wire					
Temperature rating (°C)		Intensité (A)		Text	
60 - 75		--		--	
General Use					
AC / DC	Tension (V)	Intensité (A)	Nb de phases	Nb de pôles	No. of contacts in series
AC	277	60	1	1	1
AC	600	60	1	2	1
AC	600	60	3	3	1
General Information					
Text					
- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.					

General Information						
Text						
- When intended for use as a motor disconnecter the device shall be provided with a method of being locked in the OFF-position.						
CSA						
Nominal Voltage						
			Tension (V) AC / DC			
			600 AC			
Tension assignée d'isolement Ui						
			Tension (V) AC / DC			
			600 AC			
Rated thermal current						
		Intensité (A)			Température Ambiante (°)	Additional Text
		60			0 - 40	--
Horsepower rating						
Across-the-Line Motor Starting		Tension (V)	Nb de phases	Nb de pôles	Power (HP)	Ambient temperature [°C]
DOL		110 - 120	1	2	3	40
DOL		220 - 240	1	2	7,50	40
DOL		277 - 277	1	2	7,50	40
DOL		415 - 415	1	2	10	40
DOL		440 - 480	1	2	15	40
DOL		110 - 120	3	3	5	40
DOL		220 - 240	3	3	15	40
DOL		415 - 415	3	3	20	40
DOL		440 - 480	3	3	30	40
DOL		550 - 600	3	3	40	40
Temp. rating of wire						
			Temperature rating (°C)		Intensité (A) Text	
			75		-- --	
General Use						
AC / DC	Tension (V)	Intensité (A)	Nb de phases	Nb de pôles	No. of contacts in series	
AC	277	60	1	1	1	
AC	600	60	1	2	1	
AC	600	60	3	3	1	
GENERAL TECHNICAL INFORMATION						
Tightening torque of screws						
			tightening torque (Nm)		tightening torque (lb-in)	
			1,80		16	
Stripping length						
			Length (mm) --			
			12 STRIPPINGLENGTH			
Size of conductor						
composition of conductor		Min. / Max. value	No. of conductor per terminal		Cross section (mm²) or (AWG/kcmil)	Material of the wire
flexible wire		Max.	1		AWG 6	Copper
flexible wire		Max.	1		10mm²	Copper
Single-core or stranded wire		Max.	1		AWG 6	Copper
Single-core or stranded wire		Max.	1		16mm²	Copper
flexible wire with sleeve		Max.	1		10mm²	Copper
Approbations						
Specification					Marking	
EAC						
CE marking						
UK Directives						
CSA C.22.2 No.14						
GB/T14048.3						
Recommandations concernant le tournevis						
Type		Value				
Tournevis cruciforme		PH2				
Slot screwdriver according to DIN 5264		1,2x6,5				
General Information						
Text						
- EMC Note: This device is suitable for use in environment A and B.						
- Ne jamais lubrifier ou traiter les contacts.						
- Les commutateurs ne peuvent être montés, branchés et mis en service que par une personne qualifiée selon les règles techniques en vigueur.						
- Use copper wire only. Do not coat the wire end with tin.						
- Les bornes qui ne sont pas supposées être utilisées pour le raccordement de l'appareil sont livrées serrées et ne doivent pas être desserrées. Si toutefois ces bornes sont malgré tout ouvertes accidentellement, vérifier qu'aucun shunt n'est manquant. Le câblage terminé, s'assurer que toutes les bornes sont serrées.						
Waste Electrical & Electronic Equipment (WEEE)						
Picture name		Description				
		Do not throw in the trash as care must be taken to ensure environmentally sound disposal and recycling. Please either use an environmentally friendly waste disposal company; return to the supplier for disposal; or return direct to the manufacturer, Kraus & Naimer. You can find local Kraus & Naimer offices at www.krausnaimer.com				


Proposition 65
Picture name
Description


WARNING: This product can expose you to chemicals including nickel and lead, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Type de contacts: Rigid contact bridge

Revêtement des Contacts: Silver


Types de raccordement: Screw terminal

Fixation-E


IP - Code front side		IP66, IP67
Stages		1,00 - 12,00
A	□	48,00 mm
B	∅	5,00 mm
C	∅	10,00 - 15,00 mm
D	H	<= 4,00 mm
E	∅	3,50 mm
F	H	12,20 mm
G	H	30,00 mm
H	H	64,00 mm
J	H	78,50 mm
K	H	7,40 mm
M	⌘	0,70 Nm
M1	⌘	0,90 Nm

Wiring diagram

KG64B.T903.E



Switch program

KG64B.T903.E



Kraus & Naimer


KG64B
T903
Page 1 of 1

Face Plate									
		1L1	1L2	1L3	2L1	2L2	2L3		
		1	3	5	7	9	11	13	15
									
Switching Angle 90 Total switching Angle 180		2	4	6	8	10	12	14	16
		1T1	1T2	1T3	2T1	2T2	2T3		
1	270								
0	0								
2	90								
	180								

Version: 167

Face plate

S1.F057/A1B.PEL



HANDLES

Designation: S1B.G251

Handle colour: "1" black

